

Setup Sheet CTS8 / CTS8 V2

Driver: _____

Track: _____

Car: _____

Gearing: _____

Battery: _____

Motor: _____

Timing: _____

Temp: _____

Trackconditions:

Traction: low medium high

Surface: dirt carpet clay astro

Settings	1	2	3	4	5	6	7	8	9	
Operation Mode	Forward/Brake	Forward/Brake/ Reverse	Forward/Reverse							
Initial Brake	Drag Brake	0%	6%	12%	15%	Custom				
Drag Brake	0	4	8	10	12	15	20	Custom		
Brake Strength	75%	80%	85%	90%	95%	100%				
Voltage Cut Off	None	2,9 V/cell	3,0 V/cell	3,2 V/cell	Custom					
Punch Profile	1	2	3	4	5	6	7	8	9	
Neutral Dead Band	0%	3%	6%	9%	12%					
Boost Timing	User Setting: 0° - 60° / 1° steps									
Boost Timing RPM	500	1000	1500	etc. 10. 5000	11. 6000	12. 7000	etc. 20. 15000			
BOOST Timing ACC	50 RPM/°	100 RPM/°	150 RPM/°	etc. 14. 700 RPM/°						
Reverse Speed	25%	50%	75%	100%						
Drive Frequency	2 KHZ	4 KHZ	8 KHZ	16 KHZ	32 KHZ	64 KHZ				
Brake Frequency	1 KHZ	2 KHZ	4 KHZ	8 KHZ	16 KHZ	32 KHZ				
Temperature Set	Off	176F / 80°	194F / 90°							
Reverse Rotation	Normal	Reverse								