

R10 2013 SET-UP SHEET

1/10 190mm Electric Touring Car.

ARC

RACE	
TRACK	
NAME	
CITY / COUNTRY	
DATE	


TEMPERATURE	AIR	TRACK
QUALIFYING POSITION	BEST LAPTIME SEC	FINAL POSITION
TRACK CONDITION		RACE LENGTH MIN
☐ TECHNICAL	☐ CARPET	☐ ASPHALT
☐ MIXED	☐ FAST	
TRACTION ☐ LOW ☐ MEDIUM ☐ HIGH		

FRONT	TRANSMISSION	REAR
GEAR DIFF	GEAR DIFF	GEAR DIFF
☐ ONE WAY	Number of Gears	☐ ONE WAY
☐ SPOOL	☐ 2 ☐ 4	☐ SPOOL

PINION	T	SPUR GEAR	T
R10 Internal Ratio		2.0	
FINAL DRIVE RATIO			

FRONT	SHOCK PISTON	REAR
OIL	☐ 3 HOLE	OIL
☐ 4 HOLE	HOLE SIZE	☐ 3 HOLE
CST	1.1 mm	☐ 4 HOLE
SPRING	mm	CST

	TIRES	
	RIM	
	INSERTS	
	ADDITIVE	

	Bumper Standard Cut
BODY MOUNT DISTANCE mm	

BODY	WING
------	------

NOTE

--

SHIM mm	SHIM mm	SHIM mm	SHIM mm
OFFSET STANDARD +0.75mm	SHOCK POSITION	SHOCK POSITION	OFFSET STANDARD +0.75mm
mm	FRONT	DOWNSTOP	REAR
mm			mm

Front Shock Position	Rear Shock Position
----------------------	---------------------

CAMBER
FRONT RIDE HEIGHT mm
REAR RIDE HEIGHT mm

TOE OUT IN	ANTIROLL BAR F mm	SHIM mm	ANTIROLL BAR R mm
FF BRACKET #	FR BRACKET #	BELL CRANK STANDARD 20mm Alu 22mm Alu	RF BRACKET #
			RR BRACKET #

TOPDECK mm	BATTERY FASTEN DIRECTION SIDE STANDARD
CHASSIS mm	BATTERY WEIGHT g
FR STANDARD ONE PIECE SEPARATED TYPE mm	MOTOR BULKHEAD STANDARD FLEX TYPE
FF mm	ROLLCENTER SPACER RF mm
	RR mm