

R10 2015 ATS SET-UP SHEET

ACTIVE TOE SYSTEM 1/10 190mm Electric Touring Car

ARC

RACE	
TRACK	
NAME	
CITY / COUNTRY	
DATE	

TEMPERATURE	AIR	TRACK
QUALIFYING POSITION	BEST LAP TIME	FINAL POSITION
	SEC	MIN
TRACK CONDITION		
☐ TECHNICAL	☐ CARPET	☐ ASPHALT
☐ MIXED	☐ FAST	
TRACTION		
☐ LOW	☐ MEDIUM	☐ HIGH

FRONT	TRANSMISSION	REAR
GEAR DIFF		GEAR DIFF
CST		CST
ONE WAY	Number of Gears	
SPOOL	☐ 2 ☐ 4	

PINION	T	SPUR GEAR	T
R10 Internal Ratio		2.0	
FINAL DRIVE RATIO			

FRONT	SHOCK PISTON	REAR
OIL	☐ 3 HOLE ☐ 4 HOLE	OIL
CST		CST
SPRING	HOLE SIZE	SPRING
	1.1 mm	
	mm	

	TIRES	
	RIM	
	INSERTS	
	ADDITIVE	

Bumper	
☐ Standard	☐ Cut
BODY MOUNT DISTANCE	
mm	

BODY	WING
------	------


ATS SETUP

ATS Upright Shims	
mm	
ATS Base Shims	
mm	


NOTE

SHIM	SHIM	SHIM	SHIM
mm	mm	mm	mm
OFFSET	SHOCK POSITION	SHOCK POSITION	OFFSET
STANDARD			STANDARD
+0.75mm			+0.75mm
mm	mm	mm	mm
FRONT	DOWNSTOP	REAR	

Front Shock Position



Rear Shock Position



CAMBER	
+	-
FRONT RIDE HEIGHT	REAR RIDE HEIGHT
mm	mm

TOE	ANTIROLL BAR	SHIM	ANTIROLL BAR	Rear Upright
OUT	F	mm	R	ATS 2 Hole 1 Hole
IN				
FF BRACKET	FR BRACKET	BELL CRANK	RF BRACKET	RR BRACKET
#	#	STANDARD	#	#
		20mm Alu		
		22mm Alu		

TOPDECK	BATTERY FASTEN DIRECTION	BATTERY WEIGHT	ATS Toe-In
mm	SIDE STANDARD	g	
ver			
CHASSIS			
mm			
ver			
FR	ROLL CENTER SHIMS	RF	RR
STANDARD ONE PIECE		mm	mm
SEPARATED TYPE			
mm			