

RACE

TRACK

NAME

CITY / COUNTRY

DATE

TEMPERATURE	AIR	TRACK
QUALIFYING POSITION	BEST LAP TIME SEC	FINAL POSITION
TRACK CONDITION		RACE LENGTH MIN
TRACTION		

GEAR RATIO CHART

Spur	Spur 1st			Spur 2nd		
Pinion	60	61	62	56	57	58
1st 19T	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	5.37	5.46	5.56
2nd 24T	7.26	7.38	7.51	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

SHOCK

Front: OIL 500 CST, SPRING Yellow, 1 HOLE 2 HOLE

Rear: OIL 500 CST, SPRING Blue, 1 HOLE 2 HOLE

HOLE SIZE: mm

TIRE

Front Left	32°	Tire Shore	Rear Left	35°
Front Right	32°		Rear Right	35°
Front Left	68 mm	Tire Ø	Rear Left	75 mm
Front Right	68 mm		Rear Right	75 mm

Tire Additive:

BODY

Bumper: Standard Cut

BODY MOUNT DISTANCE: 26 mm

Body: **TS030** WING: 6 mm

ENGINE

Engine	NOVA VIRTUS	Pipe	EFRA 2015
Plug	C8TGH	Carb Dia	8.5 mm
Fuel	TORNANDO	Head Shims	0.7 mm

CLUTCH

Clutch Bell	STEEL	Clutch Shoes	YELLOW
Spring Load	0.8 mm	Bell Clearance	0.6 mm

NOTE

FRONT BODY TOWER: Front Rear

DISK: Yes No

CASTER: 4 mm

WHEEL BASE: 3 mm

BUMP STEER: 0 mm

DISK: Yes No

REAR UPRIGHT SHIMS: 3 mm

ECCENTER HUB: Up Middle Low

FRONT

RIDE HEIGHT: 8 mm

DOWN STOP: +1 mm

WHEEL SHIMS: 0.8 mm

CAMBER: 1.5°

FRONT UPPER ARM: Short Medium Long

REAR

RIDE HEIGHT: 8.5 mm

DOWN STOP: +8 mm

WHEEL SHIMS: 1 mm

CAMBER: 3°

LONG SHORT: R802042 R802041

+0mm +2mm: R801021 R801022

REAR ROLL CENTER:

REAR UPPER LINK:

REAR TOE: IN 3°

FRONT TOE: OUT 1.5°

REAR ANTI-ROLL BAR: 2.6 mm

FRONT ANTI-ROLL BAR: 2.2 mm

UPPER DECK: FIX FLEX

ACKERMAN:

TRACK WIDTH: 265 mm

TRACK WIDTH: 254 mm