

RACE	TRCCA
TRACK	titan
NAME	Huang Yi Hao
CITY / COUNTRY	Taiwan
DATE	2015.9.13

TEMPERATURE	AIR	TRACK	
QUALIFYING POSITION	BEST LAPTIME	FINAL POSITION	RACE LENGTH
1	15.0 SEC	1	30 MIN
TRACK CONDITION	<input type="checkbox"/> TECHNICAL	<input checked="" type="checkbox"/> MIXED	<input type="checkbox"/> FAST
TRACTION	<input type="checkbox"/> LOW	<input checked="" type="checkbox"/> MEDIUM	<input type="checkbox"/> HIGH

### GEAR RATIO CHART

Spur	Spur 1st			Spur 2nd		
Pinion	60	61	62	56	57	58
1st 19T	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	5.37	5.46	5.56
2nd 24T	7.26	7.38	7.51	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Front		SHOCK		Rear	
OIL	<input type="checkbox"/> 1 HOLE	SHOCK PISTON	<input type="checkbox"/> 1 HOLE	OIL	<input type="checkbox"/> 1 HOLE
1000 CST	<input type="checkbox"/> 2 HOLE	HOLE SIZE	<input type="checkbox"/> 2 HOLE	1000 CST	<input type="checkbox"/> 2 HOLE
SPRING		1 mm		SPRING	
RED		1 mm		blue	

Front		TIRE		Rear	
Front Left	32°	Tire Shore	Rear Left	35°	
Front Right	32°		Rear Right	35°	
Front Left	70 mm	Tire Ø	Rear Left	77 mm	
Front Right	69 mm		Rear Right	76 mm	
		Tire Additive			

### BODY

Bumper	<input checked="" type="checkbox"/> Standard	BODY MOUNT DISTANCE	24 mm
	<input type="checkbox"/> Cut		
BODY	TS040	WING	0 mm

### ENGINE

Engine	Tesla T21	Pipe	Nova 2015
Plug	R8CGT	Carb Dia	9 mm
Fuel	Tornado	Head Shims	

### CLUTCH

Clutch Bell	Alu	Clutch Shoes	Yellow
Spring Load	5.0 mm	Bell Clearance	0.7 mm

### NOTE

2-hole front shock, 3-hole rear shock

FRONT BODY TOWER		DISK	CASTER
Front	Rear	<input checked="" type="checkbox"/> Yes	2 mm
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> No	
WHEEL BASE		BUMP STEER	
2 mm		4 mm	

DISK	REAR UPRIGHT SHIMS	
<input checked="" type="checkbox"/> Yes	4 mm	
<input type="checkbox"/> No		
ECCENTER HUB		
<input type="checkbox"/> Up	<input checked="" type="checkbox"/> Middle	<input type="checkbox"/> Low

### FRONT

RIDE HEIGHT	8 mm
DOWN STOP	+1 mm
WHEEL SHIMS	0.8 mm
CAMBER	1.5°
FRONT UPPER ARM	
<input type="checkbox"/>	Front Upper Arm Short
<input type="checkbox"/>	Front Upper Arm Medium
<input checked="" type="checkbox"/>	Front Upper Arm Long

### REAR

RIDE HEIGHT	8.5 mm
DOWN STOP	8 mm
WHEEL SHIMS	1 mm
CAMBER	3.5°

LONG	SHORT	+0mm	+2mm
<input checked="" type="checkbox"/> R802042	<input type="checkbox"/> R802041	<input checked="" type="checkbox"/> R801021	<input type="checkbox"/> R801022

REAR ROLL CENTER	REAR UPPER LINK
<input type="checkbox"/>	<input checked="" type="checkbox"/>

REAR TOE	FRONT TOE	
IN 3°	OUT 1°	
REAR ANTI-ROLL BAR	FRONT ANTI-ROLL BAR	
2.6 mm	2.8 mm	
UPPER DECK		
<input checked="" type="checkbox"/> FIX	<input type="checkbox"/> FLEX	
ACKERMAN		
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
TRACK WIDTH	TRACK WIDTH	
265 mm	254 mm	