

Firmware Version : _____ Date : _____ / _____ / _____

Track : _____ Track Temp: _____

Traction : _____ Motor : _____ Rotor : _____

Endbell : _____ Final Gear Ratio : _____

After Run

ESC Temp : _____ Motor Temp : _____

Remark : _____

Quick Setup	Blinky Mode	Modified Mode	Open Stock Mode	Off Road Mode
Throttle Value		1	5	5
TorqueFeel	15	5	15	10
Pulse Width Modulation (PWM)	4000Hz			12000Hz
Boost		off	45	off
Turbo		50	100	off
TurboDownRate		-20	-15	
Dragbrake	10%	12%	5%	5%
Compress	20%			

Advanced Setup	Blinky Mode	Modified Mode	Open Stock Mode	Off Road Mode
TorqueFineTune	Normal	Normal	Normal	Normal
Pulse Width Modulation (PWM)		14000Hz	8000Hz	
Reverse Force				35%
Compress		off	15%	5%
Boost Start		45%	15%	55%
Boost Range		42%	18%	40%
Turbo Delay		0.02s	0.02s	0.02s
Turbo Start		90%	95%	95%
Turbo Punch		Normal	4	Normal
Brake Freq	800	1000Hz	1000Hz	2000Hz
InitialBrake	60%	38%	38%	20%
Brake range	35%	55%	60%	50%
MaxBrakeForce	100	68%	68%	80%

Initial Setup	Blinky Mode	Modified Mode	Open Stock Mode	Off Road Mode
RunningMode	Forward/Brake	Forward/Brake	Forward/Brake	Forward/Brake
BatteryType	LiPo	LiPo	LiPo	LiPo
CutoffVoltage	OFF	OFF	OFF	OFF
EscOverHeat	120	120	120	120
MotorOverHeat	120	120	120	120
NeutralRange	6%	6%	6%	6%
EscMotorLink	A+B+C	A+B+C	A+B+C	A+B+C
FanMode	Auto	Auto	Auto	Auto
BEC Voltage	6v	6v	6v	6v
Motor Direction	CCW	CCW	CCW	CCW