SETUP SHEET Team Associated RC10TC3 4WD Touring Car FRONT SUSPENSION CASTER 0° 2° 4° ANTI-ROLL BAR: None Size: STOCK KICKUP 0° 2° -2° TOE-IN 0° TOE-OUT 0° CAMBER 2° RIDE HEIGHT 4MM	Driver:
REAR SUSPENSION ANTI-SQUAT 0° 2° RIDE HEIGHT 4MM ANTI-ROLL BAR: None Size: 3960 STK 4MM TOE-IN 3° Other: CAMBER: 2 ° WHEELBASE ADJUSTMENT	REAR SHOCKS BODY Composite Alum. SHAFT Std Other: LIMITERS: 4 CAMBER LINK Fill in holes used PISTON # 2 OIL 50 WT SPRING RED
REAR TIRES: FOAM Compound: PURPLE BATTERY PLACEMENT Back Front Other: CHASSIS Std Carbon Fiber FRONT/REAR DRIVE Std MOTOR BRUSH RADIO SERVO BODY WING	One-way SPUR/PINION T / T SPRING ESC (oz/gm) Indicate location:
TRACK CONDITIONS SURFACE: Smooth Bumpy TRACTION: Low Med. High COMPOSITION: Concrete Asphalt Carpet Other:	RACE COMMENTS MAIN FINISH QUALIFYING. POS NOTES:

CAR COMMENTS

NOTES: ___

NOTES: CARPET, GRAY OZITE