

TCA Setup Sheet

Driver: BOB STELLFLUE/ K. WENGER Date: 11/12/05
 Track: SOCAL RACEWAY Indoor Outdoor
 Event: STANDARD SETUP
 Conditions: INDOOR ASPHALT

Front Suspension

Ballstud: SIL
 Washers: 0
 Circle Shims (O): 2
 Triangle Shims (Δ): 2

Front Upright

Caster Block: 4
 Washers: 2
 Ballstud: SIL

Front Shocks

Piston: 2
 Oil: 50 wt
 Spring: GOLD
 Ride Height: 5 mm

Steering Rack

Ballstud: SIL
 Washers: 0

Arm Spacing

Back

 Fwd

Anti-Roll Bar

.055 - Black
 .063 - Silver
 .078 - Gold
 Other: _____

Alignment

Droop: 5.5
 Camber: -1
 Toe: 0

Front Diff

Diff Setting: _____
 Solid Axle
 Oneway

Notes: SET STEERING AT FULL THROW, THEN -10%.

Rear Suspension

Ballstud: SIL
 Washers: 1
 Square Shims (□): 2
 X Shims (X): 2

Rear Upright

Rear Shocks

Piston: 2
 Oil: 40 wt
 Spring: SILVER
 Ride Height: 5.5 mm

Turning Diameter

cm.
 ft.

Arm Spacing

Fwd

 Back

Anti-Roll Bar

.055 - Black
 .063 - Silver
 .078 - Gold
 Other: _____

Alignment

Droop: 4.5
 Camber: -1
 Toe: X 2.5

Notes: _____

Chassis Stiffness

Standoffs Spine Plate
 Notes: ALL 4 SPINE SCREWS TOP AND BOTTOM

Tires

Front Tires

Compound: SOEX 36R
 Insert: YOK 039F
 Wheel: YOK DISH
 Tire Diameter: _____
 Traction Compound: PARAGON
 Application - **Front**: FULL
 Notes: 2 WRAPS OF TAPE ON WHEEL

Rear Tires

Compound: SOEX 36R
 Insert: YOK 039F
 Wheel: YOK DISH
 Tire Diameter: _____
 Application - **Rear**: FULL

Electronics

Motor: 8X2 T1 Gear: 20 t/72 t
 Motor Brush: 729 Motor Spring: RED
 Motor Timing: 18
 Battery: REAL TIME2 3300 Position: STD
 ESC: LRP QC2 Mode: 2
 Drag Brake: 1 Initial Brake: 2

Body & Wing

Sidedams Spillplates
 Body: PROTOFORM MAZDA 6 Wing: PF, LEGAL SIZE
 Notes: _____

Race Comments

Main: _____ Qualifying Position: _____ Finish: _____
 Notes: _____