	Drfivers	Dais	
1 PA SPACE		Even18	
	Sheet Conditionss		Reval
Front Suspension		Rear Suspension	
Ride Height:	Camber:	Ride Height:	Droop:
			-
Droop:	Toe:	Ride Height Adjuster:	Axle Width:
Front Arms		Center Shock	
Upper Kingpin Shims	Lower Kingpin Shims		Shock Length
	Axle Shims		Upper Ball & Shims
		2830E	·
			Spring:
	Spring:		spring:
	Lube:		Oil:
		Damper Tubes & Side Springs	
Upper Arm Lower An Mount Spacer Spacer			Lube
Mount Spacer Spacer			
	Bumpsteer		
	Ball & Shims		<
		Spring:	Outer Ball & Shims
		Spring:	a-
	Ride Height Spacing	Preload:	
	opuing		
		Rear Pod Links	
<u>FR Shim</u> <u>RR Sh</u>	im Front Rear		•
I	Shim Shim		
<u>FR Shim</u> <u>RR Sh</u>	Shim Shim		
I	Shim Shim		Rear Link Shims
☐ 1.80° Thick Thin ☐ 3.25° Thin Thic	shim Shim n 10° k 05°		Rear Link Shims
□ 1.80° Thick Thin □ 3.25° Thin Thick □ 6.15° Thick, 1	Shim Shim n 10° k 05° Thin 0°	C Front Link Shims	Rear Link Shims
□ 1.80° Thick Thin □ 3.25° Thin Thick □ 6.15° Thick, 1 Frem Tires	Shim Shim Shim Shim n 10° k 10° k 15° Thin 10° Recr Tires	Front Link Shims Motor/Bettery	Rear Link Shims
Image: 1.80° Thick Thin Image: 3.25° Thin Thick	Shim Shim Shim Shim 10° k □ 5° Thin □ 0° Rear Tites Tire:	C Front Link Shims	
Image: style="text-align: center;">Image: style="text-align: center; style="text-align: center;">Image: style="text-align: center; style="text-align: center; style: style: style: style: style; style: s	Shim Shim Shim Shim h L 10° k D 5° Thin D 0° Recrifices Tire: Diameter: Additive Type:	Front Link Shims Motor: Timing: Generation	earing:
Image: style="text-align: center;">Image: style="text-align: center; style="text-align: center; style:	Shim Shim Shim Shim N I 10° k I 5° Thin I 0° Rear/Tires Tire: Diameter: Additive Type: Additive Amount:	Front Link Shims Motor: Timing: Battery:	earing:/
Image: symbol 1.80° Thick Thin Image: symbol 1.80° Thin Thick Image: symbol 1.80° Thin Thick, 1 Image: symbol 1.80° Thin Thin Image: symbol 1.80° Thin Thin <td< th=""><th>Shim Shim Shim Shim h L 10° k D 5° Thin D 0° Recrifices Tire: Diameter: Additive Type:</th><th>Front Link Shims Motor/Baileny Motor: Timing: Battery: Notes:</th><th>earing:/</th></td<>	Shim Shim Shim Shim h L 10° k D 5° Thin D 0° Recrifices Tire: Diameter: Additive Type:	Front Link Shims Motor/Baileny Motor: Timing: Battery: Notes:	earing:/
Image: style="text-align: center;">Image: style="text-align: center; style="text-align: center; style:	Shim Shim Shim Shim N I 10° k I 5° Thin I 0° Rear/Tires Tire: Diameter: Additive Type: Additive Amount:	Front Link Shims Mofort/Baffery/ Motor: Timing: Get Rollout: Get Battery: Notes: Radio	earing:/
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 Icomplifies Tire:	Shim Shim Shim Shim h h k 5° Thin 0° Rear/Tires Tire: Diameter: Additive Type: Additive Time:	Front Link Shims Motor//Battery Motor: Timing: Ge Rollout: Ge Battery: Notes: Radio: Ge	earing:/
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 Icomplifies Tire:	Shim Shim Shim Shim h h k 5° Thin 0° Rear/Tires Tire: Diameter: Additive Type: Additive Time:	Front Link Shims Motor//Bailteny Motor: Timing: Ge Rollout: Ge Battery: Ge Notes: Radio: Turning Circle: Steering Expo:	earing:
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 Icomplifies Tire:	Shim Shim Shim Shim h h k 5° Thin 0° Rear/Tires Tire: Diameter: Additive Type: Additive Time:	Front Link Shims Motor//Baileny Motor: Timing: Ge Rollout: Ge Battery: Ge Notes: Turning Circle: Turning Circle: Ge Steering Expo: Brake E.P.:	earing:/
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 Icomplifies Tire:	Shim Shim Shim Shim h h k 5° Thin 0° Rear/Tires Tire: Diameter: Additive Type: Additive Time:	Front Link Shims Mofort/Befflery/ Motor: Timing: Ge Rollout: Ge Battery: Ge Notes: Turning Circle: Turning Circle: Ge Steering Expo: Ge Brake E.P.: Turning Circle	earing:/
Image: system state sta	Shim Shim Shim Shim h h k 5° Thin 0° Rear/Tires Tire: Diameter: Additive Type: Additive Time:	Front Link Shims Motor//Baileny Motor: Timing: Ge Rollout: Ge Battery: Ge Notes: Turning Circle: Radio: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control	earing:/
Image: style="text-align: center;">Image: style="text-align: center;" Image: style="text-align: center;" Image: style="text-	Shim Shim	Front Link Shims Motor//Bailery Motor: Timing: Ge Rollout: Ge Battery: Ge Notes: Turning Circle: Radio: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control S.C. Type: Steering Expo:	earing:/
Image: system state	Shim Shim	Front Link Shims Motor: Timing: Get Rollout: Battery: Notes: Radio: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control S.C. Type: S.C. Settings: S.C. Software:	earing:/
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 From Thes	Shim Shim Shim Shim Shim Shim Shim Shim Near Tire: Kear Tires Tire: Diameter: Additive Type: Additive Type: Additive Time: LR RR	Front Link Shims Motor: Timing: Ger Rollout: Battery: Notes: Radio: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control S.C. Type: S.C. Settings: S.C. Software: Notes:	earing:/
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 From Tires Thick, 1 Jiameter: Additive Type: Additive Type: Additive Time: LF RF Body Body Type: Notes:	Shim Shim	Front Link Shims Motor: Timing: Ge Rollout: Ge Battery: Ge Notes: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control S.C. Type: S.C. Software: Notes: Notes:	earing:
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 Ireni files Tire: Diameter: Additive Type: Additive Time: Additive Time: LF RF Body Type: Notes: Rece and Vehicle Commenting Qualify:	Shim Shim	Front Link Shims Motor: Timing: Generation Battery: Notes: Radio: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control S.C. Type: S.C. Software: Notes: Tircck/Info Traction:	divm Low
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 From Tires Thick, 1 Jiameter: Additive Type: Additive Type: Additive Time: LF RF Body Body Type: Notes:	Shim Shim	Front Link Shims Motor: Timing: Get Rollout: Battery: Notes: Radio: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control S.C. Type: S.C. Settings: S.C. Software: Notes:	earing:
1.80° Thick Thin 3.25° Thin Thick 6.15° Thick, 1 From filtes Tire: Diameter: Additive Type: Additive Amount: Additive Time: LF RF Body Type: Notes: Rece and Vehicle Comment Qualify:	Shim Shim	Front Link Shims Motor: Timing: Get Rollout: Battery: Notes: Radio: Turning Circle: Steering Expo: Brake E.P.: Throttle Expo: Speed Control S.C. Type: S.C. Settings: S.C. Software: Notes:	dium Low