

NAME **Gabriele Vignolini**
 COUNTRY **Italy**
 RACE **C.I. UISP - Gara 4**
 TRACK **AXA Roma**

SETUP SHEET

DATE **16/09/2012** TEMP.°C AIR / TRACK /
 CARPET ASPHALT
 TRACK CONDITION TECHNICAL MIXED FAST
 TRACTION LOW MEDIUM HIGH

FRONT

1 MM
1.5 MM
0.5 MM
3 MM
1.5 MM
0 MM
80.4 gF/mm
0.0 MM

CAMBER ANGLE / ° **-1.5**
 CASTER ANGLE / ° **4**
 TOE ANGLE / ° **1**
 RIDE HEIGHT / MM **5**
 DOWNSTOP / MM **5.6**
 UPSTOP / MM **max**
 STABILIZER Ø / MM **1.0**
 LOW ARM STD
 STEERING ARM STD
 WHEEL SPACER / MM
 FRONT DRIVE BALL DIFF GEAR DIFF SPOOL ONE-WAY
 DIFF SET LOOSE MEDIUM TIGHT OIL #
 DOGBONE DRIVE BUSHING C-DRIVE BB EVD

SHOCKS SET

SPRING	STD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
DAMPER	STD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
ACTION	SYM.	<input type="checkbox"/>	ASYM. <input checked="" type="checkbox"/>
SRS/RHS ARR.	I	<input type="checkbox"/>	II <input checked="" type="checkbox"/>

REAR

2 MM
1 MM
1 MM
0 MM
1 MM
0 MM
0.5 MM
80.4 gF/mm
0.0 MM

CAMBER ANGLE / ° **-1.5**
 CASTER ANGLE / ° **5 (2 mm)**
 TOE ANGLE / ° **-3**
 RIDE HEIGHT / MM **5**
 DOWNSTOP / MM **5.2**
 UPSTOP / MM **max**
 STABILIZER Ø / MM **1.0**
 LOW ARM STD
 STEERING ARM STD
 WHEEL SPACER / MM
 REAR DRIVE BALL DIFF GEAR DIFF
 DIFF SET LOOSE MEDIUM TIGHT OIL # **650 MM**
 DOGBONE DRIVE BUSHING C-DRIVE BB EVD

SHOCKS SET

SPRING	STD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
DAMPER	STD	<input checked="" type="checkbox"/>	<input type="checkbox"/>
ACTION	SYM.	<input checked="" type="checkbox"/>	ASYM. <input type="checkbox"/>
SRS/RHS ARR.	I	<input type="checkbox"/>	II <input checked="" type="checkbox"/>

BATTERY TAPING
 ADDITIONAL WEIGHT
 CHASSIS STD
 FRAME FLEX SETTING
 TOP DECK CUT
 TOP DECK STD

FL	FR	RL	RR	TIRES	FRONT	REAR
				BRAND	Sorex 36	Sorex 36
				INSERTS	SY	SY
				WHEELS	XG	XG
				ADDITIVE	Rheinard	Rheinard

MOTOR LAYOUT	LONG.	<input checked="" type="checkbox"/>	TRANS.	<input type="checkbox"/>	MOTOR	SP V3 13.5				
SERVO LAYOUT	LEFT	<input checked="" type="checkbox"/>	RIGHT	<input type="checkbox"/>	SERVO	Sanwa				
ESC LAYOUT	LEFT	<input checked="" type="checkbox"/>	RIGHT	<input type="checkbox"/>	ESC	SP Cirtix				
BAT. LAYOUT	R1	<input type="checkbox"/>	R2	<input checked="" type="checkbox"/>	F1	<input type="checkbox"/>	F2	<input type="checkbox"/>	BATTERY	Orca
SPUR	89	PINION	41	RECEIVER	Sanwa					
FINAL DRIVE RATIO	4.52	MOTOR OFFSET / MM								
BODY	Mazda 6 Speed LW	WING	MR33							

STEERING POST

1 MM
 INNER ACKERMANN REARWARD FORWARD

BEST LAP TIME **16"999** QUALIF. / FINAL POSITION **2** / **3**
 ESC SETTING **9-1-2**
 COMMENTS / IMPRESSIONS
 CONTACT realdamon@libero.it