

Driver: Sakke Ahoniemi

Track/City: Kiiminki / Oulu

Event: Fintrack III Date: 6.3.05

Front suspension

Wishbone Aluminium Syrup damper shaft soft

Front beam - Spring 1.0 mm

Steering block on-line Stabilizer 2.1 mm glass fibre

Roll centre lowest + 0.8mm Servo position On angle post

Caster 1.5mm Steering link Centre point / middle hole

Camber - Ride height 3mm

Rear suspension

T-bar 2.1 mm glass fibre Syrup in damper pod -

Tweak Separate plate, 3rd hole On-line shock absorber VCS, 20W

Roll centre lowest + 1.6 mm Spring Soft

T-bar angle Omm Syrup in tubes diff crease

Ride height 3mm Wear width 170 mm

Others

Chassis 12M 2.4mm prototype

Front tires Corally silver star Diameter 42 mm Additive 90 %

Rear tires Corally pink Diameter 45.5mm Additive 100 %

Tire additive Jack The Gripper

Body shell CEFX Lead weights 8g

Special parts Wide rear axle, aluminium screws, protorype chassis plate

Motor Corally Black 9x2 silver Spur 99 Pinion 24

Timing 4mm Brush 4cell serrated,20%cut Spring Soft

Battery Corally GP3300 Servo Futaba 59062 Receiver battery 5 x GP170mAh

Radio Sanwa M8 ESC Corally MMS3 Program

Charger Robitronic Expert 3A, 4mV / cell

Track conditions

Surface

Traction Medium Race comments

Composition Carpet Main A Finish 1st Qualifying pos. 2nd

Temp. 21C Notes