

Driver: _____
Location: _____
Event: _____
Date: _____
Results: _____

Track Conditions

Composition: Asphalt Carpet Other: _____ Surface: Smooth Bumpy Indoor
Traction: Low High Layout: Open Both Tight Outdoor

Front End

Front spring: _____ Front ride height: _____
Front camber: _____ Toe angle: _____
King pin length: _____ Front axle: Trailing Inline
Front track width: _____

Pro-Strut front end

Caster Shim position: 0 forward 2 forward
1 forward 3 forward
Dynamic caster block: 0° 5° 10°

Ride height spacer

Coarse: 3mm 4mm 5mm
Fine: 0.25mm white 0.5mm yellow 0.75 orange

Option Parts

3277 Graphite brace
Dual Arm Long Short
Pin Brace

Front tires

Brand compound: _____
Diameter (mm): _____
Traction compound: _____
Time & surface: _____

Rear End / Center

Shock oil: _____
Center spring: _____ Preload: _____
Ball stud – front: _____
– rear: _____
Damper tube lube: _____
Side spring: _____ Preload: _____
Roll center: _____
Ride height – mid: _____ rear: _____
Pod droop: _____
Battery position: rearward forward
Rear track width: _____
Shims – left: _____ right: _____
Pod plane – unloaded : _____ loaded: _____

Rear tires

Brand compound: _____
Diameter (mm): _____
Traction compound: _____
Time & surface: _____

Body & Electronics

Body: _____
Body position: _____
Wing / Spoiler: yes no
Receiver: _____
Servo: _____

Battery: _____
Motor: _____
Gearing: _____
ESC: _____
ESC settings: _____

Comments