

Driver:
Location:
Event:
Date:
Results:

Track Conditions

Composition: Asphalt Carpet Other: Surface: Smooth Bumpy Indoor
 Traction: Low High Layout: Open Both Tight Outdoor

Front End

Front spring: Front ride height:
 Front camber: Toe angle:
 King pin length: Front axle: Trailing Inline
 Front track width:

Pro-Strut front end

Caster Shim position: 0 forward 2 forward
 1 forward 3 forward
 Dynamic caster block: 0° 5° 10°

Ride height spacer

Coarse: 3mm 4mm 5mm
 Fine: 0.25mm white 0.5mm yellow 0.75 orange

Option Parts

3277 Graphite brace
 Dual Arm Long Short
 Pin Brace

Front tires

Brand compound:
 Diameter (mm):
 Traction compound:
 Time & surface:

Rear End / Center

Shock oil:
 Center spring: Preload:
 Ball stud – front:
 – rear:
 Damper tube lube:
 Side spring: Preload:
 Roll center:
 Ride height – mid: rear:
 Pod droop:
 Rear track width:
 Shims – left: right:
 Pod plane – unloaded : loaded:
 Battery position:
 forward rearward



Rear tires

Brand compound:
 Diameter (mm):
 Traction compound:
 Time & surface:

Body & Electronics

Body:
 Body position:
 Wing / Spoiler: yes no

Receiver:
 Servo:

Battery:
 Motor:
 Gearing:
 ESC:
 ESC settings:

Comments