



Driver: _____
 Location: _____
 Event: _____
 Date: _____
 Results: _____

Track Conditions

Composition: Asphalt Carpet Other: _____ Surface: Smooth Bumpy Indoor
 Traction: Low High Layout: Open Both Tight Outdoor

Front End

Front spring: _____ Front ride height: _____
 Front camber: _____ Toe angle: _____
 King pin length: _____ Front axle: Trailing Inline
 Front track width: _____

Pro-Strut front end

Caster Shim position: 0 forward 2 forward
 1 forward 3 forward
 Dynamic caster block: 0° 5° 10°

Ride height spacer

Coarse: 3mm 4mm 5mm
 Fine: 0.25mm white 0.5mm yellow 0.75 orange

Option Parts

3277 Graphite brace
 Dual Arm Long Short
 Pin Brace

Front tires

Brand compound: _____
 Diameter (mm): _____
 Traction compound: _____
 Time & surface: _____

Rear End / Center

Shock oil: _____
 Center spring: _____ Preload: _____
 Ball stud – front: _____
 – rear: _____
 Damper tube lube: _____
 Side spring: _____ Preload: _____
 Roll center: _____
 Ride height – mid: _____ rear: _____
 Pod droop: _____
 Battery position: rearward forward inline
 Rear track width: _____
 Shims – left: _____ right: _____
 Pod plane – unloaded : _____ loaded: _____
 Chassis: _____

Rear tires

Brand compound: _____
 Diameter (mm): _____
 Traction compound: _____
 Time & surface: _____

Body & Electronics

Body: _____
 Body position: _____
 Wing / Spoiler: yes no
 Receiver: _____
 Servo: _____

Battery: _____
 Motor: _____
 Gearing: _____
 ESC: _____
 ESC settings: _____

Comments