

CK25

CALANDRA RACING CONCEPTS SETUP SHEET

Driver: Dana Bailes

Date: 11/15/18

Event: US Indoor Champs

Track: Temporary in Cleveland

Result: Qualified 2nd, finished 4th

Track Conditions

☒ CRC Black ☐ CRC Grey ☐ ETS
☐ Low ☐ Medium ☒ High
☐ Small ☒ Medium ☐ Large
☒ Smooth ☐ Both ☐ Bumpy
 Temp: 70 Humidity: low

Shock

Oil: Stock

Spring: Associated Gold

Length: _____

Preload: _____

Damper Tube

☐ 5k ☐ 10k ☐ 15k ☐ 20k

☒ 10K Hudy Silicone

Front Tires

Compound: JFT Blue stripe handout

Diameter: 39.6

Additive: SXT

Soak time: 10 min


Rear Tires

Compound: JFT Blue stripe handout

Diameter: 40.5

Additive: SXT

Soak time: 10min



Electronics

Motor: Team Scream CanAm 17.5 handout

Timing: fixed

Battery: Power Push SMC

ESC: Hobbywing XR10 Stock 1s

Ratio: 56/72

Aerodynamics


Body: Protoform Strakka

Position: Neutral

Car weight: 731

Suspended Pod: _____
(Shock lenght)


Race Ready Pod: _____
(Shock Preload)



Ride Height - Front: 3.2

Middle: 3.3

Rear: 3.5



Front Spring

☐ 45 ☒ 50 ☐ 55 ☐ 60
☐ _____

Dynamic Caster Block


☐ 0° ☒ 5° ☐ 10°



Caster


☐ 3 shims front
☒ 2 shims front
☐ 1 shim front
☐ All shims back

Camber: -.75



Roll Center Spacer

☒ 0mm
☐ 2mm
☐ 2.5mm




Side Spring Preload

0

Side Spring

☐ 45 ☐ 50 ☐ 55 ☐ 60
☒ Black Associated



Preload


Shim: none

Shim: none

Rear Steer - Shim: .060

Battery Position

☐ Forward
☒ Rearward
☐ _____



Front Brace: ☐ Yes ☒ No

Tierod Angle

☒ Swept back
☐ Swept Forward
☐ Straight

Chassis

☐ Stock Carbon
☒ Z-Flex Carbon