

SETUP TENSORIC



Driver: Lukas Stadler

Track: ERT Steyregg

Car: Associated B44.1

Gearing: 20 81

Battery: TopFuel 5500

Motor: Skalar10 6,5T

Rotor: 12,5mm

Timing: 20

Temp: 63°

ESC:

Software: V3.0_120516_MOD

Temperature: 53 °Celsius

Trackconditions:

Traction: low medium high

Temperature: 28 °Celsius

Settings	1	2	3	4	5	6	7	8	9
Running Mode	<input checked="" type="checkbox"/> Vorwärts/Bremse	<input type="checkbox"/> Vorwärts/Bremse/ Rückwärts	<input type="checkbox"/> Vor-/Rückwärts	<input type="checkbox"/> Vorwärts/Bremse 0° Timing	<input type="checkbox"/> Vorwärts/Bremse/ Rückwärts 0° Timing	<input type="checkbox"/> Vor-/Rückwärts 0° Timing	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Max. Reverse Force	<input checked="" type="checkbox"/> 25%	<input type="checkbox"/> 50%	<input type="checkbox"/> 75%	<input type="checkbox"/> 100%	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Start-Punch	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input checked="" type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
Low-Voltage Cut-Off	<input type="checkbox"/> Non-Protection	<input type="checkbox"/> 3.0V / Cell	<input type="checkbox"/> 3.2V / Cell	<input checked="" type="checkbox"/> 3.4V / Cell	<input type="checkbox"/> Custom	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Drag Brake Force	<input type="checkbox"/> 0%	<input type="checkbox"/> 5%	<input checked="" type="checkbox"/> 10%	<input type="checkbox"/> 15%	<input type="checkbox"/> 20%	<input type="checkbox"/> 25%	<input type="checkbox"/> 30%	<input type="checkbox"/> 100%	<input type="checkbox"/> Custom
Brake Force	<input type="checkbox"/> 12.5%	<input type="checkbox"/> 25%	<input type="checkbox"/> 37.5%	<input type="checkbox"/> 50%	<input type="checkbox"/> 62.5%	<input checked="" type="checkbox"/> 75%	<input type="checkbox"/> 87.5%	<input type="checkbox"/> 100%	<input type="checkbox"/>
Neutral Range	<input type="checkbox"/> Narrow	<input checked="" type="checkbox"/> Standard	<input type="checkbox"/> Wide	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Over-heat Protection	<input type="checkbox"/> enabled	<input checked="" type="checkbox"/> disabled	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Initial Brake Force	<input type="checkbox"/> =Drag Brake Force	<input checked="" type="checkbox"/> 0%	<input type="checkbox"/> 20%	<input type="checkbox"/> 40%	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Turbo Timing	10° User Setting: - 0°- 40° / 1°steps								
Turbo Slope	<input type="checkbox"/> 3° / 0.1sec	<input type="checkbox"/> 6° / 0.1sec	<input type="checkbox"/> 12° / 0.1sec	<input type="checkbox"/> 18° / 0.1sec	<input checked="" type="checkbox"/> 24° / 0.1sec	<input type="checkbox"/> Fastest	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Turbo Delay	<input type="checkbox"/> Off	<input type="checkbox"/> 0.1sec	<input type="checkbox"/> 0.2sec	<input type="checkbox"/> 0.3sec	<input checked="" type="checkbox"/> 0.4sec	<input type="checkbox"/> 0.5sec	<input type="checkbox"/> 0.6sev	<input type="checkbox"/> 0.7sec	<input type="checkbox"/> 0.8sec
BOOST Timing	0° *** FOR STOCK ONLY! *** User Setting: - 0°- 64° / 1°steps *** FOR STOCK ONLY ***								
BOOST Start RPM	1000 *** FOR STOCK ONLY! *** User Setting: 1000-1500RPM *** FOR STOCK ONLY ***								
BOOST Pressure	50RPM/Deg *** FOR STOCK ONLY! *** User Setting: 50-750RPM / 50RPM steps *** FOR STOCK ONLY ***								