

M300FX4

1/12 SCALE ELECTRIC 2WD COMPETITION CAR SETTING SHEET

☐ M300FX4

☐ M300FX4 US-spec. DATE

● Name

● Track / Event

Environment ☐ Indoor ☐ Outdoor

Surface ☐ Asphalt ☐ Carpet ☐ Bumpy ☐ Smooth

Traction ☐ Low ☐ Medium ☐ High

Air temp. °C Track temp. °C Humidity %

● Body

● Servo Mount ☐ ☆ Rear ☐ Front ☐ Floating

● Reactive Caster Angle ☐ -10° ☒ -5°

● Front Ride Height Shim ☐ 2.0mm × ☐ 1.5mm ×
☐ 1.0mm × ☐ 0.25mm ×

● Pivot Ball Position

Upper Arm

Lower Arm

● Front Spring

☐ Other ()

KM17SS	RS17R	RS17O	RS17Y	RS17B	KM17S	KM17MS	KM17	KM17H
SS	R	O	Y	B	S	MS	M	H
φ0.4(黒)	φ0.45(赤)	φ0.45(橙)	φ0.5(黄)	φ0.5(青)	φ0.45(金)	φ0.5(黒)	φ0.5(銀)	φ0.55(白)
175gf/mm	180gf/mm	200gf/mm	210gf/mm	240gf/mm	275gf/mm	330gf/mm	400gf/mm	570gf/mm

● Toe ☐ In ☐ Out

● Camber ☐ In ☐ Out

● Side Spring

RSD11 ☐ R (赤) ☐ Y (黄) ☒ B (青) ☐ W (白)

RSX211 ☐ S (銀) ☐ M (黒) ☐ H (銅)

☐ Other ()

Side Spring Tension

of turns after contact with lower brace

● Side Link ☐ Standard ☐ Other ()

● Rear Width + mm Total mm

● Ratio Pitch DP Pinion Spur T T

● Motor Rotor mm Timing Turns

● Battery / mAh

● Elect. ESC Servo Receiver

Memo

● Spacer (Roll Center) mm

● King Pin Shim

● Front Damper Oil #

● Ride Height mm

● Front Droop mm

● Caster Shim

0 0.5 1.0 1.5

1.5 1.0 0.5 0

● Front Brace ☐ Yes ☐ No

● Ackermann

1 2 3

● Servo Saver ☒ B-295 ☐ Other

● Lower Suspension Mount

-0.5 0 +0.5

● Shock Location

1 2 3 4

● Front Tire

● Front Wheel ☐ φ36 ☐ φ37 ☐ φ38

● Damper Stay Mount Location

1 2 3 4 5 6

Back Front

● Length (A) mm

● Oil #

● Spring ☐ Other ()

RSF15 ☐ S 140gf/mm ☐ M 160gf/mm ☐ H 180gf/mm

● Damper Location ☐ Front ☒ Back

● Oil #

● Ride Height mm

● Rear Droop mm

● Diameter mm

● Additive

● Time min

● Application

● Ride Height mm

● Axle Height mm

● Rear Tire

● Rear Wheel ☐ φ36 ☐ φ37 ☐ φ38