

Name 足立 伸之介 Date 2007. 7. 28 Truck / City ホビーショップみさき Event \_\_\_\_\_

#### Front Suspension

Upper Spacer 2.0 mm  
Wheel Spacer 0.5 mm  
Droop 5 mm  
Ride Height 5.0 mm

Diff. Position Front Diff.  
 Spool  
 Oneway  
 Diff.

Sus. Arm Spacer  
Front 2 mm  
Rear 1 mm  
Knuckle Spacer 0 mm

Sus. Holder Bush Front A IN / OUT A  
Rear A IN / OUT A

Sus. Holder Spacer Front 1.5mm Rear 1.5mm

Sway bar 1.0mm  
Camber Angle 1.0°

Toe Angle 0°  
Sus. Arm  TF005, TF133  
 TF005H, TF133H

#### Rear Suspension

Upper Spacer 1.5 mm  
Upper Spacer 0 mm  
Wheel Spacer 0.5 mm  
Hub Carrier Height  Up  
 Middle  
 Down  
Droop 4 mm  
Ride Height 5.3 mm

Diff. Position

Hub Carrier  
 0mm offset (SP107H)  
 1.2mm offset (TF009)  
 Aliminum (TFW002)

Hub Carrier Spacer Front 1 mm Rear 1 mm  
Sus. Arm Spacer Front 1 mm Rear 2 mm

Sus. Holder Bush Front A IN / OUT C  
Rear A IN / OUT


Sus. Holder Spacer Front 1.5 mm Rear 1.5 mm

Sway bar 1.0 mm  
Camber Angle 1.0°

Sus. Arm  TF005  
 TF005H  
 TF133 (Standard)  
 TF133H

#### Shock

|               | Front              | Rear               |
|---------------|--------------------|--------------------|
| Shock Piston  | <u>2 - C</u>       | <u>2 - C</u>       |
| Shock Oil     | <u>#35 (ORION)</u> | <u>#30 (ORION)</u> |
| Shock Spring  | <u>ブルー</u>         | <u>レッド</u>         |
| Diaphragm     | <u>std</u>         | <u>std</u>         |
| Pressure Form | <u>-</u>           | <u>-</u>           |
| Shock Length  | <u>62</u> mm       | <u>63</u> mm       |



#### Steering Wiper

#### Chassis

TF126 (Standard)  4cell  
 TFW106  5cell  
 TF103  6cell

Oneway  
 Rijid

#### Tire

| Tire  | Comments |
|---|----------|
| <u>RP36</u>   | -----    |
| Inserts <u>シルバーアロー-4. 2mS</u>                         | -----    |
| Wheel <u>タミヤ</u>                                      | -----    |
| Traction Compound 1st: <u>ツィーク</u> 2nd: <u>レッドドット</u> | -----    |

#### Others

|                             |                              |
|-----------------------------|------------------------------|
| Motor <u>ORION 刀 3ZSF</u>   | 2nd Gear Ratio : <u>1.83</u> |
| Pinion/Spur <u>29 / 99</u>  | Gear Ratio <u>6.24</u>       |
| Battery <u>ORION IB4200</u> | ESC <u>KO VFS-102</u>        |
| Body <u>マツダSPEED6</u>       | Wing <u>std</u>              |

#### Truck Condition

|  |   |
|--|---|
| <input type="checkbox"/> Smooth                  | <input checked="" type="checkbox"/> Asphalt |
| <input checked="" type="checkbox"/> Bumpy        | <input type="checkbox"/> Concrete           |
| <input checked="" type="checkbox"/> Low Traction | <input type="checkbox"/> Carpet             |
| <input type="checkbox"/> Med. Traction           | <input type="checkbox"/> Indoor             |
| <input type="checkbox"/> Higt Traction           | <input checked="" type="checkbox"/> Outdoor |

Comment : \_\_\_\_\_