

Name 基本セット Date \_\_\_\_\_ Truck / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension

Upper Spacer 2 mm  
 Wheel Spacer 0 mm  
 Droop 5 mm  
 Ride Height 5.0 mm

Diff. Position Front Diff.  
 Spool  
 Oneway  
 Diff.

Sus. Arm Spacer  
 Front 2 mm  
 Rear 1 mm  
 Knuckle Spacer 0 mm

Sus. Holder Bush  
 Front A IN / OUT A  
 Rear A IN / OUT A

Sus. Holder Spacer  
 Front 2 Rear 2

Sway bar 1.4mm  
 Toe Angle 0 °  
 Camber Angle 1.0 °

Sus. Arm  TF005, TF133  
 TF005H, TF133H

### Rear Suspension

Upper Spacer 2.0 mm  
 Upper Spacer 0 mm  
 Wheel Spacer 0 mm  
 Hub Carrier Height  
 Up  
 Middle  
 Down  
 Droop 4 mm  
 Ride Height 5.0 mm

Diff. Position

Hub Carrier  
 0mm offset (SP107H)  
 1.2mm offset (TF009)  
 Aliminum (TFW002)

Hub Carrier Spacer  
 Front 1 mm  
 Rear 1 mm  
 Sus. Arm Spacer  
 Front 1 mm  
 Rear 2 mm

Sus. Holder Bush  
 Front A IN / OUT C  
 Rear A IN / OUT E


Sus. Holder Spacer  
 Front 2 Rear 2

Sway bar 1.2mm  
 Camber Angle 1.0 °

Sus. Arm  TF005  
 TF005H  
 TF133 (Standard)  
 TF133H

### Shock

	Front	Rear
Shock Piston	2 - C	2 - C
Shock Oil	# 350	# 350
Shock Spring	ブルー	レッド
Diaphragm	std	std
Pressure Form	-	-
Shock Length	62 mm	63 mm



### Steering Wiper

### Chassis

TF126 (Standard)  4cell  
 TFW106  5cell  
 TF103  6cell

Oneway  
 Rijid

### Tire

Tire \_\_\_\_\_  
 Inserts \_\_\_\_\_  
 Wheel Traction Compound 1st: \_\_\_\_\_ 2nd: \_\_\_\_\_

Comments \_\_\_\_\_

### Others

Motor \_\_\_\_\_ 2nd Gear Ratio : 1.83  
 Pinion/Spur \_\_\_\_\_ / \_\_\_\_\_ Gear Ratio \_\_\_\_\_  
 Battery \_\_\_\_\_ ESC \_\_\_\_\_  
 Body \_\_\_\_\_ Wing \_\_\_\_\_

### Truck Condition

Smooth  Asphalt  
 Bumpy  Concrete  
 Low Traction  Carpet  
 Med. Traction  Indoor  
 Higt Traction  Outdoor

Comment :

\_\_\_\_\_

\_\_\_\_\_