

Name : _____ **Date :** _____ **Track/City :** _____ **Event :** _____

Front Suspension

Front Suspension

Shock Tower:

Upper Spacer: ☐ TFW172 (Std) 1 mm

King Pin:

☐ 97040 (Low)

☐ UM129 (Std)

Upper End:

☐ UM112H (Std)

☐ UM112

Hub Carrier:

☐ 4" (TF225H/Std)

☐ 6" (TF225-6H)

Knuckle Spacer:

☐ Upper ☐ Lower

Wheel Spacer: _____ mm

Knuckle :

☐ TF243 (TF7/Std)

☐ TF237 (TF6SP)

Drop :

☐ A ☐ B 6 mm

Sus Arm:

☐ TF268-01B (L)

☐ TF279-01 (M/Std)

☐ TF280 (S)

Sus.Holder Type:

☐ TF212 (Separates/Std)

☐ TFW120 (Onepiece)

Upper Rod Position:

☐ 0.5 mm

Diff. Position:

☐ ☐

Drive Hub :

☐ TFW113 (4.0/Std)

☐ LAW30R (4.5)

☐ TFW031 (5.2)

Ride Height: 5.2 mm

Sway Bar Holder:

☐ Plastic(TF269/Std./Cut)

☐ Plastic (TF269/Std./No Cut)

☐ Aluminum (TFW110)

ST Servo Horn:

☐ Plastic(IF435/Std.)

☐ Aluminum (IFW448/F)

☐ (IFW449/S/K)

Sus. Arm Spacer:

Front : 3 mm

Rear : 0.5 mm

Crank Bridge:

☐ Use

☐ No Use

Knuckle Spacer:

1 mm

Toe Angle: ☐ In ☐ Out 1 °

Front Diff:

☐ Spool ☐ C-joint ☐ Pin

☐ One Way

☐ Gear Diff(Oil:# _____)

(Oil Weight: _____)

Spool Cup:

☐ TFW124 (Alu.)

☐ TF287 (Steel/Std)

Sus.Holder Bushing:

Front ☐ In / Out F _____ mm

Rear ☐ In / Out F _____ mm

Swing Shaft:

☐ TF272 (Std/TFW121)

☐ TFW122 (40.5mm)

Sus. Holder Spacer:

F _____ mm

F _____ mm

Camber Angle: 2 °

Sway Bar: 1.3

15 mm

Rear Suspension

Rear Suspension

Upper Spacer: 1 mm

Shock Tower:
☐ TFW173 (Std)
☐ _____

Upper End:
☐ UM112H (Std)
☐ UM112

Upper Spacer: Texte mm

Wheel Spacer: _____ mm

Drive Hub:
☐ TFW113 (4.0/Std)
☐ LAW30R (4.5)
☐ TFW031 (5.2)

Sus. Arm:
☐ TF268-02 (L/Std.)
☐ TF279-02 (M)
☐ TF280 (S)

Sus. Holder Type (F):
☐ TF286 (Separates/std.)
☐ TF212 (Separates)
☐ TFW120 (Onepiece)

Upper Rod Position:

A.R.T.S.:
 Spacer / Outside: _____ mm
 Spacer / Inside: _____ mm

Motor Height:
☐ Up ☐ Low

Ride Height:
5,4 mm

Hub Carrier:
☐ 0° (TF225-0H)
☐ 4° (TF225H)

Sus Arm Spacer:
 Front 2,5 mm
 Rear 1 mm

Sus. Holder:
☐ TF266(Std)
☐ TF131

Diff Position:
☐

Swing Shaft:
☐ TFW032-01B (46)
☐ TF007-01 (43)

Sus. Holder Bushing:
 Front In / Out C _____ mm
 Rear In / Out B _____ mm

Droop:
☐ A ☐ B 5 mm

Sus Holder Spacer:
 Front In / Out C _____ mm
 Rear In / Out B _____ mm

Camber Angle: 2 ° **Toe Angle:** 2,5 °

Sway Bar Holder:
☐ Plastic (TF269/Std./Cut)
☐ Plastic (TF269/Std./No Cut)
☐ Aluminum (TFW10)

Sway Bar: 1,2 mm

Rear Diff:
☐ Gear Diff (Oil: # 5K)
 (Oil Weight: _____ g)
☐ Ball Diff

Shock

Shock		Front	Rear
	Piston :	6x1,2	6x1,2
	Oil :	2K	2K
	Spring :	2.8	3,2
	Diaphragm :	N	N
	Pressure Form :	NONE	NONE
	Length :	9,5 mm	9,5 mm
Outer Spacer :		mm	mm
Shock Type : ☐ W5307R (Std.) ☐			

Ackermann

Ackermann

Steering Spacer:
1,5 mm



Chassis

Chassis

Top Deck Screw:

- ☐ Steel (Std.)
- ☐ Titanium
- ☐ Aluminum

Front **Rear**

Weight: _____ g

Chassis Screws:

Battery Position:

- ☐ Front
- ☐ Rear

Weight: _____ g

Weight: _____ g

Weight: _____ g

Weight: _____ g

Center Stiffener:

- ☐ Use
- ☐ No Use

Belt Tensioner:

- ☐ TFW174

Tires & Wheels

Tire	TEAM POWER FFVRC		Comments
Insert	TEAM POWER FFVRC		
Wheel	TEAM POWER FFVRC		
Additive	1st : CS	2nd :	

Others	
--------	--

Motor REDS VX2 13.5T

Pinion/Spur 45 / 98 Gear Ratio 4.1

Battery ORION 6800 ESC REDS TX2

Body ZOO PREOPARD Wing _____

Track Condition

☐ Smooth	☐ Asphalt
☐ Bumpy	☐ Concrete
☐ Low Traction	☐ Carpet
☐ Med Traction	☐ Indoor
☐ High Traction	☐ Outdoor

Comments