

DATE	8/26/2017
DRIVER	Atsushi Hara
TRACK	Green Park Speedway

CARPET ASPHALT

TRACTION

LOW MEDIUM HIGH

LAYOUT

SLOW MIXED FAST

ELECTRIC'S

STEERING SERVO	TYPE Futaba	SETTINGS BLS571SV
ESC	TYPE Yokomo BL-PRO4	SETTINGS
ENGINE	TYPE Yokomo	SETTINGS M3 - 4.5T

TYRES/ADDITIVE	TYPE Ride REX 34S	TYPE MTG V3 Yellow
----------------	-----------------------------	------------------------------

FRONT FULL <input checked="" type="checkbox"/>	REAR FULL <input checked="" type="checkbox"/>
MIN. 5	MIN. 5

SHOCK ABSORBERS

FRONT REAR

PISTON **Kit** PISTON **Kit**

OIL **#450** OIL **#450**

SPRING **Xray 2.5-2.8** SPRING **Xray 2.6**

ANTI ROLL BAR FRONT

1,2 1,3 1,4 1,5

ANTI ROLL BAR REAR

1,1 1,2 1,3 1,4

SERVO SAVER POSITION

FORWARD REARWARD

PINION **26T** SPUR **116T**

DIFF SPOOL

HIGH LOW

DIFF OIL CST **#3,000 - 5,000 1.2g**

SHOCK POSITION LOWER ARM

PART# **Kit** PART# **Kit**

HOLE POSITION BALL LINK INSIDE OUTSIDE

FLEX

ULTRAFLEX

TOPDECK

SCREW'S ASSEMBLED

CASTER POSITION

Lower arm angle A2107A-D needs caster re-adjustment! 0.5°=0.5mm shim A2110E!

ROD POSITION SHOCK HOLE UPPER ARM POSITION

INSIDE OUTSIDE CAMBER LEFT **+2** RIGHT **+2**

SHIM(mm) **0** SHIM(mm) **0**

FF: A2105A/A2104 1pc. 2pcs.

FR: A2105B/A2104 1pc. 2pcs.

0° LOWER ARM ANGLE 0°

-0.5° -0.5° +0.5° +0.5° +0.5° +0.5° -0.5° -0.5°

KICK-UP/ANTI-DIVE

FR FF

ROLL CENTER/ TRACK WIDTH (LEFT SIDE VIEW)

5.3 (mm) 5.4 (mm)

RIDE HEIGHT DOWNSTOP

CAMBER LINK POSITION

SHIM(mm) INSIDE OUTSIDE CAMBER LEFT **+2.5** RIGHT **+2.5**

A2121 SHIM(mm) **0** SHIM(mm) **1**

RF: A2106B/A2104 1pc. 2pcs.

RR: A2106A/A2104 1pc. 2pcs.

FINAL TOE IN **3**

BOTH CENTER = 3° TOE IN

+0.5° -0.5° -0.5° -0.5° +0.5° +0.5°

KICK-UP/ANTI-DIVE

RF RR

ROLL CENTER/TOE IN/ TRACK WIDTH (RIGHT SIDE VIEW)

5.6 (mm) 4.2 (mm)

RIDE HEIGHT DOWNSTOP

A2404

ASSEMBLED SCREW'S

A2405

INSIDE SHIM(mm) **0**

OUTSIDE

TOE OUT°

WHEELBASE WEIGHT g. **10** **0** **1**

1 (mm) 1 (mm)

75.5 (mm)

10 Kit 0

WEIGHT g. CHASSIS# WEIGHT g.

STEERING SHAFT MOUNTED ON SERVOPLATE CHASSIS

STEERING STOPPER A2304/A2305/A2306 NO

WING TYPE **RC Mission**

PF LTC-R LW

BODY TYPE **8**

OVERHANG(mm)

NOTES:

タイヤウォーマー: 5分

Tire warmer: 5 min.