

**TRACK CONDITION**

ENVIRONMENT: INDOOR  OUTDOOR   
 COMPOSITION: CARPET  ASPHALT   
 TRACTION: LOW  MEDIUM  HIGH   
 LAYOUT: SLOW  MIXED  FAST   
 SURFACE: BUMPY  SMOOTH   
 NOTE: \_\_\_\_\_

**ELECTRONICS**

MOTOR: \_\_\_\_\_ TIMING: \_\_\_\_\_  
 PINION: \_\_\_\_\_ SPUR: \_\_\_\_\_  
 ESC: \_\_\_\_\_  
 BATTERY: \_\_\_\_\_  
 SERVO: \_\_\_\_\_  
 RECEIVER: \_\_\_\_\_

**SHOCK ABSORBERS**


FRONT \_\_\_\_\_ REAR \_\_\_\_\_  
 PISTON: \_\_\_\_\_ PISTON: \_\_\_\_\_  
 OIL: \_\_\_\_\_ OIL: \_\_\_\_\_  
 SPRING: \_\_\_\_\_ SPRING: \_\_\_\_\_  
 REBOUND: \_\_\_\_\_ REBOUND: \_\_\_\_\_  
 NOTE: \_\_\_\_\_

**ANTI-ROLL BAR**

FRONT: 1.2  1.3  1.4  1.5  \_\_\_\_\_   
 REAR: 1.1  1.2  1.3  1.4  \_\_\_\_\_

**TIRES & WHEELS**

TIRE: \_\_\_\_\_  
 INSERT: \_\_\_\_\_  
 WHEEL: \_\_\_\_\_  
 TREATMENT: \_\_\_\_\_  
 NOTE: \_\_\_\_\_




**SERVO SAVER POSITION**



**TRANSMISSION HEIGHT**


SPOOL \_\_\_\_\_ DIFFERENTIAL \_\_\_\_\_  
 HIGH  HIGH  OIL: \_\_\_\_\_  
 LOW  LOW

**FLEX**




**AERODYNAMICS**

BODY: \_\_\_\_\_  
 WING: \_\_\_\_\_




**CASTER POSITION**




FF: A2105A/A2104  
 1pc.  2pcs.

FR: A2105B/A2104  
 1pc.  2pcs.




KICK-UP/ANTI-DIVE



ROLL CENTER/TRACKWIDTH  
 (LEFT SIDE VIEW)

**CAMBER LINK POSITION**




RF: A2106B/A2104  
 1pc.  2pcs.


RR: A2106A/A2104  
 1pc.  2pcs.

**FINAL TOE IN**

BOTH CENTER = 3° TOE IN




KICK-UP/ANTI-DIVE





ROLL CENTER/TOE IN/  
 TRACK WIDTH  
 (RIGHT SIDE VIEW)


**A2404**



**A2405**



**STEERING SHAFT MOUNTED ON**



STEERING STOPPER A2304/A2305/A2306  
  $\phi 5$    $\phi 5,5$    $\phi 6$   NO

**NOTES:**