

# OnPoint Racing OP12C

Driver: \_\_\_\_\_  
Location: \_\_\_\_\_  
Event: \_\_\_\_\_  
Date: \_\_\_\_\_

## Track Conditions

Composition: Asphalt Carpet Other: \_\_\_\_\_ Surface: Smooth Bumpy \_\_\_\_\_  
Traction: Low High Layout: Open Both Tight Indoor Outdoor

## Front End

Associated Serpent  
Arms mount 0° 5° 10° 0° 3° 6° 10°  
Susp. arm insert Narrow / Mid / Wide  
Caster spacer 1.80° 3.25° 6.15° Front / Med / Back  
Roll centre: \_\_\_\_\_ Inside Outside  
Shims on top king pin: \_\_\_\_\_  
Front spring: \_\_\_\_\_  
Front caster: \_\_\_\_\_  
Front camber: \_\_\_\_\_  
Toe angle: \_\_\_\_\_  
Bump steer shim: \_\_\_\_\_  
Droop: \_\_\_\_\_  
King pin lube: \_\_\_\_\_  
Front car width: \_\_\_\_\_  
Ride height: \_\_\_\_\_  
Notes: \_\_\_\_\_

## Front tires

Brand & compound: \_\_\_\_\_  
Diameter: \_\_\_\_\_  
Tire treatment: \_\_\_\_\_  
Time & surface: \_\_\_\_\_

## Rear End

Shock brand: \_\_\_\_\_ Piston: \_\_\_\_\_  
Shock oil: \_\_\_\_\_  
Centre spring: \_\_\_\_\_ Preload: \_\_\_\_\_  
Shock position – Front: Low High \_\_\_\_\_  
Shock position – Rear: \_\_\_\_\_  
Damper tube lube: \_\_\_\_\_  
Side spring: \_\_\_\_\_ Preload: \_\_\_\_\_  
Rear car width: \_\_\_\_\_  
Ride height: \_\_\_\_\_  
Roll centre: \_\_\_\_\_  
Pod droop: \_\_\_\_\_  
Battery position: Left Right \_\_\_\_\_  
Plug position: Front Back \_\_\_\_\_  
Notes: \_\_\_\_\_

## Rear tires

Brand & compound: \_\_\_\_\_  
Diameter: \_\_\_\_\_  
Tire treatment: \_\_\_\_\_  
Time & surface: \_\_\_\_\_

## Body & Electronics

Body: \_\_\_\_\_  
Body position: \_\_\_\_\_  
Wing / Spoiler: Yes No \_\_\_\_\_  
Receiver: \_\_\_\_\_  
Servo: \_\_\_\_\_

Batteries: \_\_\_\_\_  
Motor: \_\_\_\_\_ Rotor: \_\_\_\_\_  
Pinion: \_\_\_\_\_ Spur: \_\_\_\_\_ Rollout: \_\_\_\_\_  
ESC: \_\_\_\_\_  
ESC Settings: \_\_\_\_\_

## Comments