

### Driver Details

Name	Marc Rheinard
Date	12/01/2020
Event / Track	IFMAR World Championship - Centre MK
Weather	-
Result	1st Place
Fastest Lap Time	

### Chassis and Electrics

Bodyshell	Mon-Tech M20
Rear Wing Height	77 mm
E.S.C	Muchmore Racing Fleta Pro v2 1s
Servo	Power HD M9
Receiver	Muchmore MRX482
LiPo	Muchmore Impact 8000

### Track Conditions

Grip Level	High <input checked="" type="checkbox"/>	Medium <input type="checkbox"/>	Low <input type="checkbox"/>
Type	Tight <input type="checkbox"/>	Open <input type="checkbox"/>	Mixed <input checked="" type="checkbox"/>
Surface	Carpet <input checked="" type="checkbox"/>	Tarmac <input type="checkbox"/>	
Condition	Smooth <input checked="" type="checkbox"/>	Bumpy <input type="checkbox"/>	
Air Temperature	14 °C		°F
Venue	Indoor <input checked="" type="checkbox"/>	Outdoor <input type="checkbox"/>	
Track Dimensions	-		

### Motor and Gearing

Motor	Muchmore Racing Fleta ZX V2 3.5t
Timing	Deg
Spur Size	94t
Pinion Size	
Rollout	mm/rev

### Tyres and Additive

Compound	Front	Control A foam 32	Rear	Control A foam 30
Diameter	Front	40.5 mm	Rear	41.5 mm
Tyre Additive	Front	Control	Rear	Control
Additive Time	Front	12 Minutes	Rear	30 Minutes
Additive Coverage	Front	half	Rear	Full
Sidewall Glue	Front	No	Rear	No

### Front

Front Ride Height	3.2 mm
Caster	4 Deg - Spacer A(Rear) 0.5 mm - Spacer B (Front) 1.0 mm
Droop	0.5 mm Droop Spacers 0.5 mm
Camber	1.5 Deg
Toe	-1.0 Deg
Inside Wheel Lock Angle	30 Deg
Outside Wheel Lock Angle	Deg
Body Post Pin Height Hole	Body on the Foam Hanger Dot Number N/A
Front Springs	<input type="checkbox"/> Black <input checked="" type="checkbox"/> Silver <input type="checkbox"/> Gold <input type="checkbox"/> White(Kit)
Front Damping Oil	10K cSt
Bump Steer Spacer	0.5 mm

### Middle

LiPo Position	<input type="checkbox"/> 1 <input type="checkbox"/> 2 <input checked="" type="checkbox"/> 3 <input type="checkbox"/> 4
Centre Damping Oil	40K cSt
Speed Secret Alloy Pivot Height Adjustment	<input checked="" type="checkbox"/> Alloy 1.0 mm <input type="checkbox"/> Kit
Side Springs	<input type="checkbox"/> Black(Kit) <input checked="" type="checkbox"/> Silver <input type="checkbox"/> Gold <input type="checkbox"/> Nickel <input type="checkbox"/> Red Dot <input type="checkbox"/> Black Ultra
Side Damping Oil	10K cSt
Topdeck Option	<input type="checkbox"/> A <input checked="" type="checkbox"/> B <input type="checkbox"/> C <input type="checkbox"/> D

### Rear

Rear Ride Height	3.5 mm - Insert 0.00 - Axle <input checked="" type="checkbox"/> Low <input type="checkbox"/> High
Droop	1.0 mm
Anti Squat	4.3 mm
Rear Axle	<input checked="" type="checkbox"/> Spool Axle <input type="checkbox"/> Ball Differential - Preload Deg
Rear Track Width	171.8 mm
Rear Axle Width Spacers Left	3 mm - Right 2 mm
Rear Spring	<input type="checkbox"/> Black <input type="checkbox"/> Silver <input type="checkbox"/> Gold <input type="checkbox"/> Nickel <input checked="" type="checkbox"/> Red Dot (Kit) <input type="checkbox"/> Black Ultra
Body Post Pin Height Hole	5 Hanger Dot Number 2
Motor Spacing	0.0 mm

### NOTES

- Speed Secrets-
- Alloy Chassis U7995
- Alloy Pivot U7918+U7919+U7897
- Spool Rear axle CR721
- Front height spacer clips U7943+U7944
- Alloy buttons and Titanium Csk Screws. CR314+CR315+CR320+CR321+CR322



-Zero side spring preload

