

Setup Sheet



DRIVER DETAILS	
NAME	
DATE	
EVENT	
LOCATION	
RACE RESULT	
QUALIFYING POSITION	
FASTEST LAP TIME	

NOTES

TRACK CONDITIONS			
GRIP LEVEL	High <input type="checkbox"/>	Medium <input type="checkbox"/>	Low <input type="checkbox"/>
TYPE	Tight <input type="checkbox"/>	Mixed <input type="checkbox"/>	Open <input type="checkbox"/>
SURFACE			
CONDITION	Smooth <input type="checkbox"/>	Bumpy <input type="checkbox"/>	
TRACK DIMENSIONS			
TEMPERATURE		°C	°F

TYRES AND ADDITIVE		
	Front	Rear
COMPOUND		
FOAM DIAMETER	mm	mm
TYRE ADDITIVE		
ADDITIVE TIME	minutes	minutes
ADDITIVE COVERAGE	%	%
SIDEWALL GLUE	<input type="checkbox"/>	<input type="checkbox"/>

MOTOR AND GEARING	
MOTOR	
MOTOR OPTIONS	
ROTOR DIAMETER	
TIMING	
SPUR GEAR SIZE	
PINION SIZE	
ROLLOUT	mm / rev

ELECTRICS AND BODYSHELL	
BODYSHELL	HEIGHT mm
E.S.C	
SERVO	
RECEIVER	
LiPo	

FRONT	
CAMBER	degrees
RIDE HEIGHT	mm
RIDE HEIGHT SPACER	1.0mm <input type="checkbox"/> 1.5mm <input type="checkbox"/> 2mm <input type="checkbox"/>
TOE OUT	degrees/side
DAMPING	cSt
DROOP	mm
FRONT END BRACE	O-ring <input type="checkbox"/> Solid <input type="checkbox"/> Removed <input type="checkbox"/>

STATIC CASTER

FRONT	REAR	STATIC CASTER
<input type="checkbox"/> 1.5mm	<input type="checkbox"/> 0mm	<input type="checkbox"/> 2.5°
<input type="checkbox"/> 1mm	<input type="checkbox"/> 0.5mm	<input type="checkbox"/> 4.0° (kit)
<input type="checkbox"/> 0.5mm	<input type="checkbox"/> 1mm	<input type="checkbox"/> 6.0°
<input type="checkbox"/> 0mm	<input type="checkbox"/> 1.5mm	<input type="checkbox"/> 7.5°

UPPER ARM LENGTH

SPACER.....mm

REACTIVE CASTER

5°

10°

SPACER.....mm

SHIMS.....mm

SHIMS.....mm

SHIMS.....mm

FRONT TRACK WIDTH ADJUSTMENT

OUTBOARD

SHIMS.....mm

FRONT TRACK WIDTH INBOARD

-0.5mm

0.0mm

+0.5mm

- FRONT SPRINGS**
- SUPER SOFT - U7013
 - RED - U7015
 - YELLOW - U7016
 - BLUE - U7014
 - SOFT - U7012
 - MEDIUM SOFT - U7011
 - MEDIUM - U7009
 - HARD - U7010

REAR	
RIDE HEIGHT	mm
ROLL DAMPING	cSt
BUMP DAMPING	cSt
DROOP	mm
ROLL CENTRE SHIFT	KIT <input type="checkbox"/> +2.5mm <input type="checkbox"/>mm <input type="checkbox"/>
ANTI SQUAT	KIT <input type="checkbox"/> ANTI SQUAT <input type="checkbox"/>
DIFF PRELOAD	360° KIT <input type="checkbox"/>° <input type="checkbox"/>

SPACERS.....mm/side

TRACK WIDTH.....mm

ROLL SPRINGS (SIDE)

SOFTER ← → HARDER

U4838 BLACK U4839 SILVER U4840 GOLD U4841 NICKEL

BUMP SPRING (CENTRE)

SOFTER ← → HARDER

U4838 BLACK U4839 SILVER U4840 GOLD U4841 NICKEL