

### DRIVER DETAILS

NAME Chris Grainger  
 DATE August 2014  
 EVENT Euros  
 WEATHER warm/dry  
 RESULT

### NOTES

ti balls  
 ti turnbuckles  
 ti shock shafts  
 core rc alloy screws



### CHASSIS AND ELECTRICS

CHASSIS std Rear Motor  Mid Motor   
 TOP DECK 2.5mm  
 BODYSHELL LTCR  
 WING Mr33  
 E.S.C Hobbywing  
 SERVO KO  
 RECIEVER KO  
 CELLS GM  
 CELL POSITION Forward  Rearward

### MOTOR AND GEARING

MOTOR 4.5T  
 ROTOR DIAMETER 12.5  
 TIMING STD  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 89  
 PINION SIZE 22

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  30 °F   
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS Revlite  
 TYRES Sorex 40  
 INSERTS Yellow  
 TYRE ADDITIVE Mr33  
 ADDITIVE TIME Front 15 Minutes Rear 15 Minutes  
 TYRE WARMERS Yes  No  Temp 60 °C Time 15 Minutes

### FRONT

Spool  
 Gear Diff  
 Diff Oil ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Washers 1.5mm  
 Droop..... 5.5mm  
 On 10mm Block   
 Ride Height ..... 5.5mm  
 Camber..... -1.5 Degree's  
 Toe-in..... Degree's  
 Toe-out..... 1 Degree's

Washers 0.5mm  
 Washers ..... 1mm

Washers 0mm

Washers ..... 1mm

4° Yoke  
 6° Yoke  
 SERVO SAVER Yes   
 No

Washers ..... 0mm  
 X=..... 0mm

Washers ..... 0mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... 450 cTs  
 SPRING green .....  
 PISTON std .....  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE.....mm  
 SHOCK LENGTH (X).....mm  
 REBOUND 0 .....%

Alloy  Steel  Double Joint

### REAR

Ball Diff  
 Gear Diff  
 Diff Oil ..... 2000 cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Droop..... 4.5mm  
 On 10mm Block   
 Ride Height ..... 5.8mm  
 Camber..... -2 Degree's

Washers ..... 1mm

Washers 1mm  
 Washers ..... 1mm

Washers ..... 0mm

Washers 0.75mm

WheelBase  Short  
 Middle  
 Long

(2 Pip shown)  
 0 Groove  
 1 Groove  
 2 Groove

Washers ..... 0mm

Washers ..... 0mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... 450 cTs  
 SPRING green .....  
 PISTON std .....  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE.....mm  
 SHOCK LENGTH (X).....mm  
 REBOUND 0 .....%

Alloy  Steel