

DRIVER DETAILS

NAME **Chris Grainger**
 DATE **Feb '14**
 EVENT **Asphalt Testing**
 WEATHER **Dry**
 RESULT **N/A**

NOTES

Uncut Arms



CHASSIS AND ELECTRICS

CHASSIS **Std** Rear Motor Mid Motor
 TOP DECK **2mm**
 BODYSHELL **LTC-R**
 WING **Schumacher**
 E.S.C **GM**
 SERVO **KO**
 RECIEVER **KO**
 CELLS **GM**
 CELL POSITION Forward Rearward

MOTOR AND GEARING

MOTOR **4.5**
 ROTOR DIAMETER **Std**
 TIMING **Std**
 GEAR PITCH 48DP 64DP
 SPUR SIZE **89**
 PINION SIZE **22**

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C **25** °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS **Schumacher Revlite**
 TYRES **Sorex**
 INSERTS **Yellow**
 TYRE ADDITIVE **No**
 ADDITIVE TIME Front Minutes Rear Minutes
 TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers **1.5**mm
 Droop... **4.5**mm
 On 10mm Block
 Ride Height **4.5**mm
 Camber... **2** Degree's
 Toe-in..... Degree's
 Toe-out... **1** Degree's

Washers **0.5**mm
 Washers **1.0**mm

Washers **0**mm

4° Yoke
 6° Yoke
 SERVO SAVER Yes
 No

7075-T8
 Washers **1.0**mm
 X= **0**mm

CAP TYPE Vented Sealed Emulsion
 OIL... **450** cTs
 SPRING... **Green**
 PISTON... **Kit (3x1.1mm)**
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....mm
 SHOCK LENGTH (X)... **10.5**mm
 REBOUND **100**%

REAR

Ball Diff
 Gear Diff
 Diff Oil **1.000** cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop... **3.5**mm
 On 10mm Block
 Ride Height **5**mm
 Camber... **2** Degree's
 Washers **1.0**mm
 Washers **0.5**mm

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers **0**mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove
 Washers **1.0**mm
 WheelBase
 Short
 Middle
 Long

CAP TYPE Vented Sealed Emulsion
 OIL... **450** cTs
 SPRING... **Green**
 PISTON... **kit (3x1.1mm)**
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....mm
 SHOCK LENGTH (X)... **10.5**mm
 REBOUND **100**%

Alloy Steel