

### DRIVER DETAILS

NAME chris Grainger  
 DATE brca agm!!  
 EVENT ews round 1  
 WEATHER  
 RESULT 3rd

### NOTES

cut arms  
 ff arm brace  
 rr arm brace



### CHASSIS AND ELECTRICS

CHASSIS std Rear Motor  Mid Motor   
 TOP DECK 2.5 with front post  
 BODYSHELL protoform speed 6 lw  
 WING mr33  
 E.S.C hw  
 SERVO ko  
 RECIEVER ko  
 CELLS interlect  
 CELL POSITION Foward  Rearward

### MOTOR AND GEARING

MOTOR hw 4.5  
 ROTOR DIAMETER 12.5  
 TIMING std  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 89  
 PINION SIZE 21

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  20 °F   
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS ride  
 TYRES ride  
 INSERTS rride  
 TYRE ADDITIVE lrp 2  
 ADDITIVE TIME Front 15 Minutes Rear 15 Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### FRONT

Spool  
 Gear Diff  
 Diff Oil ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Washers 1 .....mm  
 Droop.....5.5mm  
 On 10mm Block   
 Ride Height .....5.2mm  
 Camber.....2.....Degree's  
 Toe-in.....Degree's  
 Toe-out.....1.....Degree's

Washers 0.5 .....mm  
 Washers 2 .....mm

Washers .....mm

4° Yoke  
 6° Yoke  
 Yes   
 No   
 SERVO SAVER

Washers 0 .....mm  
 X=0 .....mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL 450 .....cTs  
 SPRING schumacher blue  
 PISTON std  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE .....mm  
 SHOCK LENGTH (X).....11 .....mm  
 REBOUND 0 .....%

Alloy  Steel  Double Joint

### REAR

Ball Diff  
 Gear Diff  
 Diff Oil 1000 ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Droop.....4.2mm  
 On 10mm Block   
 Ride Height .....5.5mm  
 Camber.....2.....Degree's  
 Washers 0.5 .....mm

(2 Pip shown)  
 0 Pip 3.0°  
 1 Pip 2.5°  
 2 Pip 2.0°

Washers 0 .....mm

(2 Pip shown)  
 0 Groove  
 1 Groove  
 2 Groove  
 Washers 1 .....mm  
 WheelBase  
 Short  
 Middle  
 Long  
 CAP TYPE Vented  Sealed  Emulsion   
 OIL 450 .....cTs  
 SPRING schumacher white  
 PISTON std  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE .....mm  
 SHOCK LENGTH (X).....11 .....mm  
 REBOUND 0 .....%

Alloy  Steel