

**DRIVER DETAILS**

NAME Ed Clark  
 DATE 28 June 2014  
 EVENT Logan Clubbie  
 WEATHER Cold, cold, cold  
 RESULT Q1, F1

**NOTES**

Cut Arms F&R  
 FF and RR Wishbone straps fitted



**CHASSIS AND ELECTRICS**

CHASSIS Kit Rear Motor  Mid Motor   
 TOP DECK 2mm + U4605 brace  
 BODYSHELL LTC-R Lwt  
 WING MR33  
 E.S.C Hobbywing V3  
 SERVO Sanwa ERG BLS  
 RECIEVER Sanwa 451R  
 CELLS ProAmps 6000  
 CELL POSITION Foward  Rearward

**MOTOR AND GEARING**

MOTOR Hobbywing V10 4.5t  
 ROTOR DIAMETER 12.5  
 TIMING 30°  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 118  
 PINION SIZE 26

**TRACK CONDITIONS**

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  10 °F   
 VENUE Indoor  Outdoor

**WHEELS, TYRES AND INSERTS**

WHEELS MuchMore  
 TYRES Rush 36  
 INSERTS MuchMore  
 TYRE ADDITIVE MR  
 ADDITIVE TIME Front 15 Minutes Rear 15 Minutes  
 TYRE WARMERS Yes  No  Temp 60 °C Time 10 Minutes

**FRONT**

Spool  
 Gear Diff  
 Diff Oil ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Washers 1.5 mm  
 Droop..... 5.5 mm  
 On 10mm Block   
 Ride Height ..... 5.4 mm  
 Camber..... 1.5 Degree's  
 Toe-in..... 1.0 Degree's  
 Toe-out..... 1.0 Degree's

Washers 1.5 mm  
 Washers 1.0 mm

Washers 0.0 mm

Washers 0.5 mm  
 Washers 0.5 mm

4° Yoke  
 6° Yoke  
 Yes   
 No   
 SERVO SAVER

Washers ..... 3.0 mm  
 X=..... 0.0 mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... MuchMore 450 ..... cTs  
 SPRING Schumacher Green  
 PISTON 3 x 1.1mm  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... 11.0 mm  
 REBOUND 0 %

Alloy  Steel  Double Joint

**REAR**

Ball Diff  
 Gear Diff  
 Diff Oil ..... 2000 ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Droop..... 4.5 mm  
 On 10mm Block   
 Ride Height ..... 5.6 mm  
 Camber..... 2.0 Degree's  
 Washers ..... 1.0 mm

Washers 0.0 mm

Washers 1.0 mm

(2 Pip shown)  
 0 Groove  
 1 Groove  
 2 Groove

Washers ..... 0.0 mm

WheelBase  
 Short  
 Middle  
 Long

Alloy  Steel

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... MuchMore 450 ..... cTs  
 SPRING Schumacher Green  
 PISTON 3 x 1.1mm  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... 11.0 mm  
 REBOUND 0 %