

DRIVER DETAILS

NAME Ed Clark
 DATE 09 Aug 2014
 EVENT Logan Club race
 WEATHER Cool
 RESULT Q2, F2

CHASSIS AND ELECTRICS

CHASSIS 2.5mm Kit Rear Motor Mid Motor
 TOP DECK 2.5mm + U4605 Front Stiffener
 BODYSHELL LTC-R Lwt
 WING MR33
 E.S.C Hobbywing V3
 SERVO Sanwa ERG-BLS
 RECIEVER Sanwa 451R
 CELLS ProAmps 6000
 CELL POSITION Forward Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 18 °F
 VENUE Indoor Outdoor

NOTES

Cut Wishbones F&R
 U4601 Wishbone Straps in FF and RR positions only.
 Fast! Very good all through the corner.
 Go to 0.5mm under rear inner link to free car up in higher traction.



MOTOR AND GEARING

MOTOR Hobbywing V10 4.5t
 ROTOR DIAMETER 12.5mm
 TIMING 30°
 GEAR PITCH 48DP 64DP
 SPUR SIZE 118
 PINION SIZE 27

WHEELS, TYRES AND INSERTS

WHEELS MuchMore
 TYRES Rush 36
 INSERTS MuchMore Yellow
 TYRE ADDITIVE MR33
 ADDITIVE TIME Front 15 Minutes Rear 15 Minutes
 TYRE WARMERS Yes No Temp 60 °C Time 10 Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1.5 mm
 Droop.....5.5...mm
 On 10mm Block
 Ride Height5.2...mm
 Camber.....1.5...Degree's
 Toe-in.....Degree's
 Toe-out.....0.75...Degree's

Washers 1.5 mm
 Washers 1.0 mm

Washers 0.0 mm

Washers 0.5 mm
 Washers 0.5 mm

4° Yoke
 6° Yoke
 SERVO SAVER
 Yes
 No

Washers2.0...mm
 X=.....0.0...mm

CAP TYPE Vented Sealed Emulsion
 OIL.....MuchMore 450.....cTs
 SPRING Schumacher Green
 PISTON 3 x 1.1mm
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....mm
 SHOCK LENGTH (X).....11.0...mm
 REBOUND 0.....%

REAR

Ball Diff
 Gear Diff
 Diff Oil2000.....cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop.....4.5...mm
 On 10mm Block
 Ride Height5.4...mm
 Camber.....2.0...Degree's

Washers 1.0 mm

Washers 0.0 mm

Washers 1.0 mm
 Washers 1.0 mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove

Washers 1.0 mm
 WheelBase
 Short
 Middle
 Long

CAP TYPE Vented Sealed Emulsion
 OIL.....MuchMore 450.....cTs
 SPRING Schumacher Green
 PISTON 3 x 1.1mm
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....mm
 SHOCK LENGTH (X).....11.0...mm
 REBOUND 0.....%