

DRIVER DETAILS

NAME Nikolai Håheim
 DATE 15-11/2014
 EVENT NWS RD1
 WEATHER
 RESULT TQ and Win

NOTES

Stiffner brace in top deck.
 25 grams in front bumper
 Lot of onpower steering.
 Balanced turn in and good mid corner steering



CHASSIS AND ELECTRICS

CHASSIS STD Rear Motor Mid Motor
 TOP DECK 2,0mm
 BODYSHELL Mazda 6 LW
 WING Schumacher
 E.S.C Fleta Pro
 SERVO KO RSX
 RECIEVER Futaba
 CELLS MuchMore
 CELL POSITION Foward Rearward

MOTOR AND GEARING

MOTOR 5T
 ROTOR DIAMETER 12,5
 TIMING 20
 GEAR PITCH 48DP 64DP
 SPUR SIZE 114
 PINION SIZE 26

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS Revlite
 TYRES Sorex 28
 INSERTS JB
 TYRE ADDITIVE Nosram Carpet
 ADDITIVE TIME Front 30 Minutes Rear 30 Minutes
 TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1mm
 Droop.....5.6mm
 On 10mm Block
 Ride Height5.0mm
 Camber.....2 Degree's
 Toe-in.....Degree's
 Toe-out.....1 Degree's

Washers 1.5 mm
 Washers 1 mm

Washers 0 mm

4° Yoke
 6° Yoke
 Yes
 No
 SERVO SAVER

Washers 1 mm
 X=.....0 mm

CAP TYPE Vented Sealed Emulsion
 OIL.....450 cTs
 SPRING.....Yokomo Pink
 PISTON.....STD
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....mm
 SHOCK LENGTH (X).....11.0 mm
 REBOUND °.....%

Alloy Steel Double Joint

REAR

Ball Diff
 Gear Diff
 Diff Oil 3000 cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop.....4.4mm
 On 10mm Block
 Ride Height5.5mm
 Camber.....1.5 Degree's
 Washers 1 mm
 Washers 0.5 mm

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers 0 mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove
 Washers 1 mm
 WheelBase Short
 Middle
 Long
 CAP TYPE Vented Sealed Emulsion
 OIL.....450 cTs
 SPRING.....Yokomo Blue
 PISTON.....STD
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....mm
 SHOCK LENGTH (X).....11.0 mm
 REBOUND °.....%

Alloy Steel