

DRIVER DETAILS

NAME *Robert Krens*
 DATE *20-06-2014*
 EVENT *Pre Nationals Amca*
 WEATHER *Hot, 35degC,*
 RESULT *TQ and win. 24 in 7:04. FL 17,68*

NOTES

Mi5EVO
 race winning innovation
 Alterations by Arn0 at PetitRC.com



CHASSIS AND ELECTRICS

CHASSIS *Std* Rear Motor Mid Motor
 TOP DECK *Std*
 BODYSHELL *Mazda Speed 6 GX*
 WING *Std, 10 mm over, middle cut down*
 E.S.C *Much More Fleta Euro*
 SERVO *Futaba 9551*
 RECIEVER *Sanwa 451R*
 CELLS *Dualsey 6200 90c*
 CELL POSITION Forward Rearward

MOTOR AND GEARING

MOTOR *Much More Fleta 13,5t*
 ROTOR DIAMETER *12,3*
 TIMING *Fixxee*
 GEAR PITCH 48DP 64DP
 SPUR SIZE *96*
 PINION SIZE *43*

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C °F *50segC*
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS *Ride REX 34*
 TYRES
 INSERTS
 TYRE ADDITIVE *MG yellow*
 ADDITIVE TIME Front *20* Minutes Rear *20* Minutes
 TYRE WARMERS Yes No Temp *70* °C Time *10* Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers *2* mm
 Droop.....*2* mm
 On 10mm Block
 Ride Height*5.2* mm
 Camber.....*2.1* Degree's
 Toe-in.....Degree's
 Toe-out.....*1* Degree's

Washers *1* mm
 Washers *1* mm

Washers *1* mm

4° Yoke
 6° Yoke
 Yes
 No
 SERVO SAVER

Washers*2* mm
 7076-T6

Washers *0.5* mm
 Washers *0.5* mm
 CAP TYPE Vented Sealed Emulsion
 OIL.....*500* cTs
 SPRING.....*HPI Pink*
 PISTON *#3*
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....*1.1* mm
 SHOCK LENGTH (X).....*11* mm
 REBOUND*0* %

Alloy Steel Double Joint

X=.....*0* mm

REAR

Ball Diff
 Gear Diff
 Diff Oil*800* cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop.....*3* mm
 On 10mm Block
 Ride Height*5.4* mm
 Camber.....*2* Degree's
 Washers *1* mm
 Washers *0.7* mm
 Washers *0.7* mm

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers *0* mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove
 Washers *1.5* mm
 WheelBase
 Short
 Middle
 Long
 CAP TYPE Vented Sealed Emulsion
 OIL.....*400* cTs
 SPRING.....*Schumi green*
 PISTON *#3*
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....*1.1* mm
 SHOCK LENGTH (X).....*11* mm
 REBOUND*0* %

Alloy Steel