

DRIVER DETAILS

NAME Robert Krens
 DATE 28-07-2014
 EVENT Dutch Nationals #4 - AMCA Apeldoorn
 WEATHER Summer, sunny, 25degC
 RESULT 24R in 5:10. FL17.3

CHASSIS AND ELECTRICS

CHASSIS Rear Motor Mid Motor
 TOP DECK STD
 BODYSHELL Speed 6 GX
 WING STD wing cut down in the middel
 E.S.C Much More Fleta Euro's
 SERVO Futaba 9551
 RECIEVER Sanw 451R
 CELLS Dualsky 6200
 CELL POSITION Foward Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 34 °F
 VENUE Indoor Outdoor

NOTES

Speed 6 is more easy, but slower. Don't let the tires get dry. HPI silver and Rear Shocks more angled doesn't work. Awesome set-up for cold weather. When hotter: 1.2 stabi rear. 2.5 degree toe rear. 0,7mm rollcenter rear



MOTOR AND GEARING

MOTOR Much More Fleta 13,5T
 ROTOR DIAMETER 12.3mm
 TIMING "Zero" (12deg)
 GEAR PITCH 48DP 64DP
 SPUR SIZE 96
 PINION SIZE 43

WHEELS, TYRES AND INSERTS

WHEELS Ride Rex 34
 TYRES Ride Rex 34
 INSERTS Ride Rex 34
 TYRE ADDITIVE MG V3 Yellow
 ADDITIVE TIME Front 20 Minutes Rear 20 Minutes
 TYRE WARMERS Yes No Temp 70 °C Time 15 Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 2 mm
 Droop..... 2mm
 On 10mm Block
 Ride Height 5.1mm
 Camber..... 2.1 Degree's
 Toe-in..... Degree's
 Toe-out..... Degree's

Washers 1 mm
 Washers 1 mm

Washers 0.5 mm

4° Yoke
 6° Yoke
 Yes
 No
 SERVO SAVER

Washers 1.5 mm

Alloy Steel Double Joint

X=..... 0mm

CAP TYPE Vented Sealed Emulsion
 OIL..... (35WT) 450cTs
 SPRING..... HPI Pink
 PISTON... #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1mm
 SHOCK LENGTH (X)..... 11mm
 REBOUND 0%

REAR

Ball Diff
 Gear Diff
 Diff Oil 800cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop..... 3mm
 On 10mm Block
 Ride Height 5.4mm
 Camber..... 2.1 Degree's

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers 0mm

Alloy Steel

Washers 1.5 mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove
 Washers 1.5mm
 WheelBase
 Short
 Middle
 Long

CAP TYPE Vented Sealed Emulsion
 OIL..... (30WT) 375cTs
 SPRING..... Schumi Green
 PISTON... #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1mm
 SHOCK LENGTH (X)..... 11mm
 REBOUND 0%