

DRIVER DETAILS

NAME Robert Krens
 DATE 03-10-2015
 EVENT Local Race
 WEATHER Dry, Sunny, 18°C
 RESULT TQ + Win. FL17.020 25R in 7:17

CHASSIS AND ELECTRICS

CHASSIS STD Rear Motor Mid Motor
 TOP DECK STD + extra siffner
 BODYSHELL Protoform Mazda Speed 6. 3mm forward
 WING STD
 E.S.C Much More Fleta euro
 SERVO Futaba 9551
 RECIEVER Sanwa 451R
 CELLS Dualsky 6200
 CELL POSITION Foward Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 21 °F
 VENUE Indoor Outdoor

NOTES

2015 Shocktowers
 2015 Steering rack
 2015 Spool
 Roche Dual Joints

Car is awesome fast! Broke track record. Switched Wheel hexes. big at front

Mi5 EVO
 race winning innovation

Schumacher
 racing-cars.com

MOTOR AND GEARING

MOTOR Much More Fleta 13,5T
 ROTOR DIAMETER Blue 12,3mm
 TIMING Fixxed ~ 12°
 GEAR PITCH 48DP 64DP
 SPUR SIZE 96
 PINION SIZE 38

WHEELS, TYRES AND INSERTS

WHEELS Sorex BRCA
 TYRES Sorex 32R
 INSERTS BRCA Yellow
 TYRE ADDITIVE TireTweak
 ADDITIVE TIME Front 15 Minutes Rear 15 Minutes
 TYRE WARMERS Yes No Temp 70 °C Time 15 Minutes

FRONT

Spool
 Gear Diff

Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1.5 mm

Droop..... 39.1 (2)mm
 On 10mm Block

Ride Height 5.4mm
 Camber..... 2.0 Degree's
 Toe-in..... Degree's
 Toe-out..... 0.5 Degree's

Washers 1 mm

Washers 0.5 mm

Washers 0 mm

4° Yoke
 6° Yoke

Yes
 No

SERVO SAVER

Washers 2 mm

X=..... 0 mm

CAP TYPE Vented Sealed Emulsion
 OIL..... 500cTs
 SPRING..... HPI Pink
 PISTON..... #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1mm
 SHOCK LENGTH (X)..... 10mm
 REBOUND 0 %

REAR

Ball Diff
 Gear Diff

Diff Oil 2000 cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1.5 mm

Droop..... 37.8 (3)mm
 On 10mm Block

Ride Height 5.6mm
 Camber..... 1.8 Degree's

(2 Pip shown)

0 Groove
 1 Groove
 2 Groove

Washers 1.5 mm

Washers 0.5 mm

Washers 1 mm

Washers 1 mm

Washers 2 mm

X=..... 0 mm

CAP TYPE Vented Sealed Emulsion
 OIL..... 450cTs
 SPRING..... HPI Silver
 PISTON..... #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1mm
 SHOCK LENGTH (X)..... 10mm
 REBOUND 0 %

Alloy Steel

Alloy Steel

0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

(2 Pip shown)

Diff Oil 2000 cTs

Ball Diff
 Gear Diff

