

### DRIVER DETAILS

NAME Robert Krens  
 DATE 12-04-2015  
 EVENT CW #1 - HFCC  
 WEATHER Sunny, Dry, 19°C  
 RESULT TQ + Win. 25L - 7:13.075 FL17.426

### CHASSIS AND ELECTRICS

CHASSIS Rear Motor  Mid Motor   
 TOP DECK STD + Extra front brace  
 BODYSHELL Montech Nazda 3  
 WING STD  
 E.S.C Much More Fleta Euro's  
 SERVO Futaba 9551  
 RECIEVER Sanwa 451R  
 CELLS Dualsky 6200Mah 90C  
 CELL POSITION Foward  Rearward

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  °F   
 VENUE Indoor  Outdoor

### NOTES

- Good Starting set-up.  
 Really fast on cold track. Bit loose on warmer track.  
 - Rear end doesn't react quick enough trough chicanes, but is alright.  
 - 2015 Shocktowers  
 - Extreme ring of death....?



### MOTOR AND GEARING

MOTOR Much More Fleta 13,5T 'type W'  
 ROTOR DIAMETER 12.3mm  
 TIMING "Zero Degree"  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 96  
 PINION SIZE 38

### WHEELS, TYRES AND INSERTS

WHEELS Sorex  
 TYRES Sorex 32R  
 INSERTS Yellow (BRCA)  
 TYRE ADDITIVE TC5 + LG1  
 ADDITIVE TIME Front 100% Minutes Rear 100% Minutes  
 TYRE WARMERS Yes  No  Temp 70 °C Time 25 Minutes

### FRONT

Spool  
 Gear Diff

Diff Oil ..... cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Washers ..... 1.5mm

Dropo.....1.5mm  
 On 10mm Block

Ride Height ..... 5.8mm  
 Camber.....2° Degree's  
 Toe-in.....Degree's  
 Toe-out.....1° Degree's

Washers ..... 1.5mm

Washers ..... 0mm

Washers ..... 1mm

4° Yoke  
 6° Yoke

Yes   
 No

SERVO SAVER

Washers ..... 1.5mm

X=.....0mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL.....300 cTs  
 SPRING.....Schumacher Green  
 PISTON...#3  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE.....1.1mm  
 SHOCK LENGTH (X).....10.54mm  
 REBOUND 0.....%

### REAR

Ball Diff  
 Gear Diff

Diff Oil ..... 800 cTs

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm  
 6 Dot - 1.6mm

Dropo.....2.5mm  
 On 10mm Block

Ride Height ..... 6.0mm  
 Camber.....1.5 Degree's

Washers ..... 1mm

Washers ..... 1mm

Washers ..... 1mm

(2 Pip shown)

0 Groove  
 1 Groove  
 2 Groove

Washers .....mm

WheelBase  
 Short  
 Middle  
 Long

Washers ..... 1mm

X=.....mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL.....350 cTs  
 SPRING.....Schumacher Green  
 PISTON...#3  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE.....1.1mm  
 SHOCK LENGTH (X).....10.54mm  
 REBOUND 0.....%