

DRIVER DETAILS

NAME Robert Krens
 DATE 10-06-2015
 EVENT Avond wedstrijd
 WEATHER Warm, Sunny, 20degC
 RESULT TQ and Win 25L in 7:11 FL 17.305

CHASSIS AND ELECTRICS

CHASSIS Rear Motor Mid Motor
 TOP DECK STD + extra stiffner
 BODYSHELL Montech Nazda 3
 WING STD
 E.S.C MuchMore Fleta Euro's
 SERVO Futaba 9551
 RECIEVER Sanwa 451R
 CELLS Dualsky 6250Mah
 CELL POSITION Foward Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 23 °F
 VENUE Indoor Outdoor

NOTES

2015 Shoktowers
 Twinpoint Steering
 LightWeight spool



MOTOR AND GEARING

MOTOR Much More Fleta 13,5T
 ROTOR DIAMETER Blue
 TIMING Fixed
 GEAR PITCH 48DP 64DP
 SPUR SIZE 96
 PINION SIZE 39

WHEELS, TYRES AND INSERTS

WHEELS Sorex 32 BRCA
 TYRES Sorex 32 BRCA
 INSERTS Sorex 32 BRCA
 TYRE ADDITIVE TireTweak
 ADDITIVE TIME Front 20 Minutes Rear 20 Minutes
 TYRE WARMERS Yes No Temp 80 °C Time 20 Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1.5 mm
 Droop.....1.5.....mm
 On 10mm Block
 Ride Height5.4.....mm
 Camber.....2.....Degree's
 Toe-in..........Degree's
 Toe-out.....0.5.....Degree's

Washers 1 mm
 Washers 1.5 mm

Washers 0.5 mm

4° Yoke
 6° Yoke
 SERVO SAVER Yes No

Washers 1.0 mm

Alloy Steel Double Joint

X=.....0.....mm

CAP TYPE Vented Sealed Emulsion
 OIL.....300.....cTs
 SPRING.....Schumi Green.....
 PISTON...#3.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....1.1.....mm
 SHOCK LENGTH (X).....11.....mm
 REBOUND 0.....%

REAR

Ball Diff
 Gear Diff
 Diff Oil 800 cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop.....2.5.....mm
 On 10mm Block
 Ride Height5.8.....mm
 Camber.....1.5.....Degree's

Washers 1 mm

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers 0 mm

Alloy Steel

WheelBase Short Middle Long

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove

Washers 1.5 mm

CAP TYPE Vented Sealed Emulsion
 OIL.....350.....cTs
 SPRING.....Schumi Green.....
 PISTON...#3.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....1.1.....mm
 SHOCK LENGTH (X).....11.....mm
 REBOUND 0.....%