

DRIVER DETAILS

NAME Robert Krens
 DATE 12-08-2015
 EVENT Avond CW #6
 WEATHER Dry, sunny, good weather. 25°C
 RESULT TQ and win

CHASSIS AND ELECTRICS

CHASSIS Rear Motor Mid Motor
 TOP DECK STD
 BODYSHELL Montech Nazda 3.0
 WING STD
 E.S.C Much More Fleeta 'Euro's'
 SERVO Futaba 9551
 RECIEVER Sanwa 451R
 CELLS Dualsky 6200Mah
 CELL POSITION Foward Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 28°C °F
 VENUE Indoor Outdoor

NOTES

Twin point steering
 2015 Shocktowers
 Roche Dual Joints
 2015 Spool
 Drive Freq 8Hz
 Brake Freq 4Hz
 Power #12
 Brake on transmitter 94%



MOTOR AND GEARING

MOTOR Much More Fleeta 13,5T
 ROTOR DIAMETER 12,3mm Purple
 TIMING 'Fixed' ~ 12°
 GEAR PITCH 48DP 64DP
 SPUR SIZE 96
 PINION SIZE 38

WHEELS, TYRES AND INSERTS

WHEELS Sorex 32R 'BRCA'
 TYRES Sorex 32
 INSERTS Yellow
 TYRE ADDITIVE MR33
 ADDITIVE TIME Front 20 Minutes Rear 20 Minutes
 TYRE WARMERS Yes No Temp 70 °C Time 20 Minutes

FRONT

Spool
 Gear Diff

Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1.5 mm

Droop.....1.5.....mm
 On 10mm Block

Ride Height 5.8.....mm
 Camber..... 2.....Degree's
 Toe-in..........Degree's
 Toe-out.....1.....Degree's

Washers 1 mm

Washers 0.5 mm

Washers 0 mm

Washers 0.5 mm

4° Yoke
 6° Yoke

Yes
 No

SERVO SAVER

Washers 1.5 mm

7075-T6

X=.....0.....mm

Alloy Steel Double Joint

CAP TYPE Vented Sealed Emulsion
 OIL.....300.....cTs
 SPRING.....Schumacher Green.....
 PISTON...#3.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....1.1.....mm
 SHOCK LENGTH (X).....11.....mm
 REBOUND 0.....%

REAR

Ball Diff
 Gear Diff

Diff Oil 800 cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1.2 mm

Droop.....2.5.....mm
 On 10mm Block

Ride Height 6.2.....mm
 Camber..... 2.....Degree's

Washers 1 mm

Washers 1.5 mm

Washers 1 mm

(2 Pip shown)

0 Groove
 1 Groove
 2 Groove

Washers 1.5 mm

WheelBase
 Short
 Middle
 Long

Alloy Steel

CAP TYPE Vented Sealed Emulsion
 OIL.....3.5.....cTs
 SPRING.....Schumacher Green.....
 PISTON...#3.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....1.1.....mm
 SHOCK LENGTH (X).....11.....mm
 REBOUND 0.....%