

DRIVER DETAILS

NAME Robert Krens
 DATE 05-07-2015
 EVENT Dutch Nationals #3 - MRM Lelystad
 WEATHER Dry, hot, sunny 25°C
 RESULT TQ + Win. FL21,389 19R in 7:06

CHASSIS AND ELECTRICS

CHASSIS 2.5mm Rear Motor Mid Motor
 TOP DECK STD + Front brace
 BODYSHELL Montech Nazda 3 LW
 WING JG Racing Wide wing
 E.S.C Much More Fleta Euro's
 SERVO Futaba 9551
 RECIEVER Sanwa 451R
 CELLS Dualsky 6250Mah
 CELL POSITION Foward Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 36 °F
 VENUE Indoor Outdoor

NOTES

Front Rollcenter 1.5 -> Les reaction, better high speed grip
 Bumpsteer 1 -> 0,5mm more rotation.
 10 gram aligned with spurgear 48DP!!! Car is awesome!
 '2015' shocktowers, steering rack and dualjoints



MOTOR AND GEARING

MOTOR Much More Fleta 13,5T
 ROTOR DIAMETER 12.3mm
 TIMING "Zero Degree" ~ 12°
 GEAR PITCH 48DP 64DP
 SPUR SIZE 74
 PINION SIZE 26 = 5.12

WHEELS, TYRES AND INSERTS

WHEELS Ride Rex 26027 (ver 2015)
 TYRES Ride Rex 26027 (ver 2015)
 INSERTS Ride Rex 26027 (ver 2015)
 TYRE ADDITIVE TC5+LG1
 ADDITIVE TIME Front 15 Minutes Rear 15 Minutes
 TYRE WARMERS Yes No Temp 80 °C Time 15 Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 2.0 mm
 Droop 1.5 (39.1) mm
 On 10mm Block
 Ride Height 5.3 mm
 Camber 1.8 Degree's
 Toe-in Degree's
 Toe-out Degree's

Washers 1 mm
 Washers 0.5 mm

Washers 0 mm

4° Yoke
 6° Yoke
 SERVO SAVER Yes No

Washers 2.0 mm
 X = mm

CAP TYPE Vented Sealed Emulsion
 OIL 300 cTs
 SPRING Schumacher Green
 PISTON #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE 1.10 mm
 SHOCK LENGTH (X) 10 mm
 REBOUND %

REAR

Ball Diff
 Gear Diff
 Diff Oil 800 cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 1.2 mm
 Droop 3.0 (37.8) mm
 On 10mm Block
 Ride Height 5.6 mm
 Camber 2.2 Degree's

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers 1.0 mm

Alloy Steel

Washers 1.5 mm
 WheelBase Short Middle Long

CAP TYPE Vented Sealed Emulsion
 OIL 350 cTs
 SPRING Schumi Green
 PISTON #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE 1.10 mm
 SHOCK LENGTH (X) 10 mm
 REBOUND %