

DRIVER DETAILS

NAME Robert Krens
 DATE 31-08-2014
 EVENT Dutch Nationals #4 - Real 80 Groningen
 WEATHER Wet, Cold,
 RESULT 18,3FL

CHASSIS AND ELECTRICS

CHASSIS Rear Motor Mid Motor
 TOP DECK STD
 BODYSHELL Speed 6 LW (Better then GX)
 WING JG Hard wide wing - 10mm over
 E.S.C Much More Fleta Euro's
 SERVO Futaba 9551
 RECIEVER Sanwa 451R
 CELLS Dualsky 6200
 CELL POSITION Foward Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 27 °F
 VENUE Indoor Outdoor

NOTES

Yoko Pink all around really good over bumps, but really easy. Schumi green, faster, but harder over the bumps

4K diff oil better then 2K

Speed 6 much better then GX



MOTOR AND GEARING

MOTOR Much More Fleta 13,5T
 ROTOR DIAMETER 12.3
 TIMING STD ~ 12deg
 GEAR PITCH 48DP 64DP
 SPUR SIZE 96
 PINION SIZE 43

WHEELS, TYRES AND INSERTS

WHEELS Ride Rex 34
 TYRES Ride Rex 34
 INSERTS Ride Rex 34
 TYRE ADDITIVE LRP Carpet 2 (TC5+LG1 doesn't work)
 ADDITIVE TIME Front 20 Minutes Rear 20 Minutes
 TYRE WARMERS Yes No Temp 60 °C Time 20 Minutes

FRONT

Spool
 Gear Diff
 Diff Oil cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Washers 2 mm
 Droop..... 3mm
 On 10mm Block
 Ride Height 5.8mm
 Camber..... 2Degree's
 Toe-in..... 2Degree's
 Toe-out..... 1Degree's

Washers 1 mm
 Washers 1 mm

Washers 0mm

4° Yoke
 6° Yoke
 SERVO SAVER Yes No

Washers 1.5 mm

Alloy Steel Double Joint

X=..... 0mm

CAP TYPE Vented Sealed Emulsion
 OIL..... 300cTs
 SPRING... Yokomo Pink
 PISTON... #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1mm
 SHOCK LENGTH (X)..... 11mm
 REBOUND 0%

REAR

Ball Diff
 Gear Diff
 Diff Oil 4000cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm
 6 Dot - 1.6mm

Droop..... 4mm
 On 10mm Block
 Ride Height 6mm
 Camber..... 2Degree's

(2 Pip shown)
 0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°

Washers 1mm

Alloy Steel

WheelBase Short Middle Long

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove
 Washers 1mm
 CAP TYPE Vented Sealed Emulsion
 OIL..... 350cTs
 SPRING... Yokomo Pink
 PISTON... #3
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1mm
 SHOCK LENGTH (X)..... 11mm
 REBOUND 0%