

### DRIVER DETAILS

NAME  
DATE  
EVENT  
WEATHER  
RESULT

### NOTES



### CHASSIS AND ELECTRICS

CHASSIS Rear Motor  Mid Motor   
TOP DECK  
BODYSHELL  
WING  
E.S.C  
SERVO  
RECIEVER  
CELLS  
CELL POSITION Foward  Middle  Rearward

### MOTOR AND GEARING

MOTOR  
ROTOR DIAMETER  
TIMING  
GEAR PITCH 48DP  64DP   
SPUR SIZE  
PINION SIZE

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
TYPE Tight  Open  Mixed   
SURFACE Carpet  Tarmac   
CONDITION Smooth  Bumpy   
TEMPERATURE °C  °F   
VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS  
TYRES  
INSERTS  
TYRE ADDITIVE  
ADDITIVE TIME Front Minutes Rear Minutes  
TYRE WARMERS Yes  No  Temp °C Time Minutes

### REAR

Ball Diff  
 Gear Diff

Diff Oil ..... cTs

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Droop.....mm  
On 10mm Block

Ride Height .....mm  
Camber.....Degree's

Washers Under Ball  
 Washers Under Bracket  
.....mm

Washers .....mm

3 Groove 39mm  
 4 Groove 37mm

(4 Groove shown)

Washers .....mm

(2 Pip shown)

0 Groove  
 1 Groove  
 2 Groove

CAP TYPE Vented  Sealed  Emulsion   
OIL.....cTs  
SPRING.....  
PISTON.....  
DRILLED Yes  No   
DRILLED PISTON HOLE SIZE.....mm  
SHOCK LENGTH (X).....mm  
REBOUND .....

0 Pip 3.0°  
 1 Pip 2.5°  
 2 Pip 2.0°

(2 Pip shown)

Alloy  Steel

### FRONT

Spool  
 Gear Diff

Diff Oil ..... cTs

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Washers Under Ball  
 Washers Under Bracket  
.....mm

Droop.....mm  
On 10mm Block

Ride Height .....mm  
Camber.....Degree's  
Toe-in.....Degree's  
Toe-out.....Degree's

Washers .....mm

3 Groove 39mm  
 4 Groove 37mm

(4 Groove shown)

Washers .....mm

Washers .....mm

CAP TYPE Vented  Sealed  Emulsion   
OIL.....cTs  
SPRING.....  
PISTON.....  
DRILLED Yes  No   
DRILLED PISTON HOLE SIZE.....mm  
SHOCK LENGTH (X).....mm  
REBOUND .....

4° Yoke  
 6° Yoke

Yes   
No

SERVO SAVER

Washers .....mm

Alloy  Steel  Double Joint