

DRIVER DETAILS

NAME
DATE
EVENT
WEATHER
RESULT

NOTES



CHASSIS AND ELECTRICS

CHASSIS Rear Motor Mid Motor
TOP DECK
BODYSHELL
WING
E.S.C
SERVO
RECIEVER
CELLS
CELL POSITION Forward Middle Rearward

MOTOR AND GEARING

MOTOR
ROTOR DIAMETER
TIMING
GEAR PITCH 48DP 64DP
SPUR SIZE
PINION SIZE

TRACK CONDITIONS

GRIP LEVEL High Medium Low
TYPE Tight Open Mixed
SURFACE Carpet Tarmac
CONDITION Smooth Bumpy
TEMPERATURE °C °F
VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS
TYRES
INSERTS
TYRE ADDITIVE
ADDITIVE TIME Front Minutes Rear Minutes
TYRE WARMERS Yes No Temp °C Time Minutes

REAR

Ball Diff
 Gear Diff

Diff Oil cTs

3 Groove 39mm
 4 Groove 37mm
(4 Groove shown)

0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°
(2 Pip shown)

Alloy Steel

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Droop.....mm
On 10mm Block

Ride Heightmm
Camber.....Degree's

Washers Under Ball
 Washers Under Bracket
.....mm

Washersmm

Washersmm

0 Groove
 1 Groove
 2 Groove
(2 Pip shown)

Washersmm

WheelBase
 Short
 Middle
 Long

CAP TYPE Vented Sealed Emulsion

OIL.....cTs

SPRING.....

PISTON.....

DRILLED Yes No

DRILLED PISTON HOLE SIZE.....mm

SHOCK LENGTH (X).....mm

REBOUND.....

FRONT

Spool
 Gear Diff

Diff Oil cTs

3 Groove 39mm
 4 Groove 37mm
(4 Groove shown)

4° Yoke
 6° Yoke

Yes
No
SERVO SAVER

Alloy Steel Double Joint

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Washers Under Ball
 Washers Under Bracket
.....mm

Droop.....mm
On 10mm Block

Ride Heightmm
Camber.....Degree's
Toe-in.....Degree's
Toe-out.....Degree's

Washersmm

Washersmm

Washersmm

Washersmm

CAP TYPE Vented Sealed Emulsion

OIL.....cTs

SPRING.....

PISTON.....

DRILLED Yes No

DRILLED PISTON HOLE SIZE.....mm

SHOCK LENGTH (X).....mm

REBOUND.....