

### DRIVER DETAILS

NAME Jan Eichhorn  
 DATE 08-06-2013  
 EVENT  
 WEATHER  
 RESULT

### NOTES

Front and rear belt 2 steps looser from standard.

Need to try 3 groove plates front and rear with maybe a little softer front spring, and 2,5 rear toe-in.



### CHASSIS AND ELECTRICS

CHASSIS standard Rear Motor  Mid Motor   
 TOP DECK standard, 2 posts  
 BODYSHELL Mazda speed 6 LW  
 WING Standard  
 E.S.C SP cirtix club stock  
 SERVO Ko propo rsx one  
 RECIEVER Sanwa  
 CELLS IP 7200  
 CELL POSITION Forward  Middle  Rearward

### MOTOR AND GEARING

MOTOR SP 13,5  
 ROTOR DIAMETER 12,3  
 TIMING 10  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 74  
 PINION SIZE 33

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  15 °F   
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS  
 TYRES Ride / soresx 32  
 INSERTS  
 TYRE ADDITIVE RH  
 ADDITIVE TIME Front Minutes Rear Minutes  
 TYRE WARMERS Yes  No  Temp 65 °C Time 20 Minutes

### REAR

Ball Diff  
 Gear Diff  
 Diff Oil ..... 1000 cTs

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Droop..... 3 mm  
 On 10mm Block   
 Ride Height ..... 5.2 mm  
 Camber..... 1.5 Degree's  
 Washers Under Ball  
 Washers Under Bracket ..... 2 mm

Washers ..... 0.5 mm

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

Washers ..... 0.5 mm

0 Groove  
 1 Groove  
 2 Groove  
 (2 Pip shown)

Washers ..... 1 mm

WheelBase  
 Short  
 Middle  
 Long

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... MR33 450 cTs  
 SPRING..... HPI silver  
 PISTON..... standard  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... 12.4 mm  
 REBOUND 2 mm

0 Pip 3.0°  
 1 Pip 2.5°  
 2 Pip 2.0°  
 (2 Pip shown)

Alloy  Steel

### FRONT

Spool  
 Gear Diff  
 Diff Oil ..... cTs

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Washers Under Ball  
 Washers Under Bracket ..... 0.5 mm  
 Droop..... 4 mm  
 On 10mm Block   
 Ride Height ..... 5.7 mm  
 Camber..... 2 Degree's  
 Toe-in..... Degree's  
 Toe-out..... 0.8 Degree's

Washers ..... 0 mm

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

Washers ..... 0 mm

Washers ..... 1 mm

Washers ..... 1 mm

WheelBase  
 Short  
 Middle  
 Long

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... MR33 450 cTs  
 SPRING..... HPI gold  
 PISTON..... standard  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... 12.4 mm  
 REBOUND 2 mm

4° Yoke  
 6° Yoke  
 Yes   
 No   
 SERVO SAVER

Washers ..... 0 mm

Alloy  Steel  Double Joint