

### DRIVER DETAILS

NAME *Jimmy maddison*  
 DATE *12.1.14*  
 EVENT *EWS*  
 WEATHER  
 RESULT *TQ and Win*

### NOTES



### CHASSIS AND ELECTRICS

CHASSIS *2mm* Rear Motor  Mid Motor   
 TOP DECK *Std with 2 braces*  
 BODYSHELL *Bitty design Nardo*  
 WING *V2*  
 E.S.C *Muchmore fleta euro*  
 SERVO *Sanwa*  
 RECIEVER *Sanwa*  
 CELLS  
 CELL POSITION Forward  Middle  Rearward

### MOTOR AND GEARING

MOTOR *Muchmore fleta zx 17.5*  
 ROTOR DIAMETER *12.5*  
 TIMING *32 degrees*  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE *90*  
 PINION SIZE *41*

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  °F   
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS  
 TYRES *Sorex 32*  
 INSERTS  
 TYRE ADDITIVE *Sxt*  
 ADDITIVE TIME Front *20* Minutes Rear *20* Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### REAR

Ball Diff  
 Gear Diff  
 Diff Oil *1500* cTs

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

0 Pip 3.0°  
 1 Pip 2.5°  
 2 Pip 2.0°  
 (2 Pip shown)

Alloy  Steel

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Droop..... *4* mm  
 On 10mm Block

Ride Height..... *5.2* mm  
 Camber..... *2* Degree's

Washers Under Ball  
 Washers Under Bracket  
 ..... *1* mm

Washers ..... *0.5* mm

Washers ..... *0.5* mm

0 Groove  
 1 Groove  
 2 Groove  
 (2 Pip shown)

Washers ..... *1* mm

WheelBase  
 Short  
 Middle  
 Long

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... *450* cTs  
 SPRING..... *Green*  
 PISTON..... *Std*  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... mm  
 REBOUND *50%*

### FRONT

Spool  
 Gear Diff  
 Diff Oil ..... cTs

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

4° R  
 6° Yoke  
 Yes  No   
 SERVO SAVER

Alloy  Steel  Double Joint

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Washers Under Ball  
 Washers Under Bracket  
 ..... *0* mm

Droop..... *5* mm  
 On 10mm Block

Ride Height..... *5* mm  
 Camber..... *1.5* Degree's  
 Toe-in..... Degree's  
 Toe-out..... *1* Degree's

Washers ..... *0.5* mm

Washers ..... *0* mm

Washers ..... *5* mm

Washers ..... *1* mm

Washers ..... *1* mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... *450* cTs  
 SPRING..... *Green*  
 PISTON..... *Std*  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... mm  
 REBOUND *50%*