

### DRIVER DETAILS

NAME Martin Hofer  
 DATE 26./28.04.13  
 EVENT LRP Touring Car Masters 2013  
 WEATHER rainy  
 RESULT 13th

### CHASSIS AND ELECTRICS

CHASSIS kit Rear Motor  Mid Motor   
 TOP DECK kit  
 BODYSHELL Speed 6 LW, 5mm forward  
 WING MR33, 17mm high, 10mm overhang  
 E.S.C GM Genius Pro (timing 2+5)  
 SERVO GM HGM SLP  
 RECIEVER Sanwa 451R  
 CELLS GM V-Maxx  
 CELL POSITION Forward  Middle  Rearward

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  20 °F   
 VENUE Indoor  Outdoor

### NOTES

glued flat part of the tire sidewall

# Mi5

**Schumacher**  
 racing-cars.com

### MOTOR AND GEARING

MOTOR GM Race 5.5T  
 ROTOR DIAMETER standard  
 TIMING middle  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE 114  
 PINION SIZE 26

### WHEELS, TYRES AND INSERTS

WHEELS handout  
 TYRES VTEC CPX  
 INSERTS handout  
 TYRE ADDITIVE LRP carpet 2  
 ADDITIVE TIME Front 20 Minutes Rear 20 Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### REAR

Ball Diff  
 Gear Diff  
 Diff Oil ..... 3000 cTs

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Droop..... 4.5 mm  
 On 10mm Block   
 Ride Height ..... 5.2 mm  
 Camber..... 2.0 Degree's  
 Washers Under Ball  
 Washers Under Bracket ..... 1.5 mm  
 Washers ..... 1.0 mm

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

Washers ..... 1.0 mm

(2 Pip shown)  
 0 Groove  
 1 Groove  
 2 Groove  
 Washers ..... 1.0 mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... 450 cTs  
 SPRING..... Yokomo Blue  
 PISTON..... kit  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... 10.5 mm  
 REBOUND 10%.....

0 Pip 3.0°  
 1 Pip 2.5°  
 2 Pip 2.0°  
 (2 Pip shown)

Alloy  Steel

### FRONT

Spool  
 Gear Diff  
 Diff Oil ..... cTs

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Washers Under Ball  
 Washers Under Bracket ..... 1.0 mm  
 Droop..... 5.0 mm  
 On 10mm Block   
 Ride Height ..... 5.0 mm  
 Camber..... 1.5 Degree's  
 Toe-in..... Degree's  
 Toe-out..... 1.0 Degree's  
 Washers ..... 1.0 mm

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

Washers ..... 0 mm

Washers ..... 1.0 mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL..... 450 cTs  
 SPRING..... Yokomo Pink  
 PISTON..... kit  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE..... mm  
 SHOCK LENGTH (X)..... 10.5 mm  
 REBOUND 10%.....

4° Yoke  
 6° Yoke  
 SERVO SAVER Yes  No

Washers ..... 0 mm

Washers ..... 1.0 mm

Alloy  Steel  Double Joint