

DRIVER DETAILS

NAME Martin Hofer
 DATE 01.08. - 04.08.
 EVENT EFRA Euros 2013 Portugal
 WEATHER HOT!
 RESULT

NOTES

cut front arms, rear brace



CHASSIS AND ELECTRICS

CHASSIS 2.5mm Rear Motor Mid Motor
 TOP DECK 2.0mm
 BODYSHELL PF Speed 6 LW 5mm forward
 WING MR33, 17 high, 10 over
 E.S.C GM Genius Pro
 SERVO GM HGM SLP
 RECIEVER Sanwa 451R
 CELLS Gm V-Maxx 99024
 CELL POSITION Forward Middle Rearward

MOTOR AND GEARING

MOTOR GM Race 4.5
 ROTOR DIAMETER standard
 TIMING 2+3
 GEAR PITCH 48DP 64DP
 SPUR SIZE 114
 PINION SIZE 28

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 55 °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS VTEC
 TYRES 33X
 INSERTS handout
 TYRE ADDITIVE -
 ADDITIVE TIME Front Minutes Rear Minutes
 TYRE WARMERS Yes No Temp °C Time Minutes

REAR

Ball Diff
 Gear Diff
 Diff Oil 2000 cTs

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Droop..... 4.0 mm
 On 10mm Block
 Ride Height 5.0 mm
 Camber..... 1.5 Degree's
 Washers Under Ball
 Washers Under Bracket 1.0 mm
 Washers 1.0 mm

3 Groove 39mm
 4 Groove 37mm
 (4 Groove shown)

Washers 0.5 mm

(2 Pip shown)
 0 Groove
 1 Groove
 2 Groove
 Washers 1.0 mm
 WheelBase
 Short
 Middle
 Long

CAP TYPE Vented Sealed Emulsion
 OIL..... 500 cTs
 SPRING..... Green
 PISTON..... standard
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1 mm
 SHOCK LENGTH (X)..... 10.5 mm
 REBOUND 10%.....

0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°
 (2 Pip shown)

Alloy Steel

FRONT

Spool
 Gear Diff
 Diff Oil cTs

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Washers Under Ball
 Washers Under Bracket 0.5 mm
 Droop..... 4.5 mm
 On 10mm Block
 Ride Height 5.2 mm
 Camber..... 2.0 Degree's
 Toe-in..... Degree's
 Toe-out..... 0.5 Degree's
 Washers 0.5 mm

3 Groove 39mm
 4 Groove 37mm
 (4 Groove shown)

Washers 0 mm

Washers 1.0 mm
 Washers 1.0 mm

CAP TYPE Vented Sealed Emulsion
 OIL..... 500 cTs
 SPRING..... Green
 PISTON..... standard
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1 mm
 SHOCK LENGTH (X)..... 10.5 mm
 REBOUND 10%.....

4° Yoke
 6° Yoke
 Yes No
 SERVO SAVER

Alloy Steel Double Joint

Washers 0 mm