

DRIVER DETAILS

NAME *Martin Hofer*
 DATE *15.-16.06.13*
 EVENT *ETS Rd. 3 Traiskirchen / Austria*
 WEATHER *Hot*
 RESULT *3rd*

CHASSIS AND ELECTRICS

CHASSIS *standard* Rear Motor Mid Motor
 TOP DECK *standard, no front post*
 BODYSHELL *PF Speed 6 LW, 5mm forward*
 WING *Mr33, 17mm high, 10mm overhang*
 E.S.C *handout*
 SERVO *GM HGM SLP (SHR mode)*
 RECIEVER *Sanwa*
 CELLS *GM V-Maxx*
 CELL POSITION Forward Middle Rearward

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C °F *30*
 VENUE Indoor Outdoor

NOTES

*hoff-spec steering plates,
 2.0deg rear wishbone
 in A3, very good as it
 was "free-er" in those
 highbite conditions*

Mi5

Schumacher
 racing-cars.com

MOTOR AND GEARING

MOTOR *handout*
 ROTOR DIAMETER *std*
 TIMING *fixed*
 GEAR PITCH 48DP 64DP
 SPUR SIZE *96*
 PINION SIZE *38*

WHEELS, TYRES AND INSERTS

WHEELS *handout*
 TYRES *Ride REX34*
 INSERTS
 TYRE ADDITIVE *Mighty Grip*
 ADDITIVE TIME Front *25* Minutes Rear *25* Minutes
 TYRE WARMERS Yes No Temp *70* °C Time *20* Minutes

REAR

Ball Diff
 Gear Diff
 Diff Oil *2000* cTs

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Droop.....*4.0*...mm
 On 10mm Block
 Ride Height.....*5.2*...mm
 Camber.....*2.0*...Degree's

Washers Under Ball
 Washers Under Bracket
*2.0*...mm

Washers*0.5*...mm

3 Groove 39mm
 4 Groove 37mm
 (4 Groove shown)

Washers*1.0*...mm

0 Groove
 1 Groove
 2 Groove
 (2 Pip shown)

Washersmm

WheelBase
 Short
 Middle
 Long

CAP TYPE Vented Sealed Emulsion
 OIL.....*600*...cTs
 SPRING...*Schumacher green*.....
 PISTON...*standard*.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....*1.10*...mm
 SHOCK LENGTH (X).....*10.6*...mm
 REBOUND *20%*.....

0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°
 (2 Pip shown)

Alloy Steel

FRONT

Spool
 Gear Diff
 Diff Oil cTs

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Washers Under Ball
 Washers Under Bracket
*1.5*...mm

Droop.....*5.0*...mm
 On 10mm Block
 Ride Height.....*5.0*...mm
 Camber.....*1.5*...Degree's
 Toe-in.....Degree's
 Toe-out.....*1.0*...Degree's

Washers*0.5*...mm

3 Groove 39mm
 4 Groove 37mm
 (4 Groove shown)

Washersmm

Washers*1.5*...mm

Washers*1.0*...mm

Washersmm

WheelBase

CAP TYPE Vented Sealed Emulsion
 OIL.....*550*...cTs
 SPRING...*Schumacher green*.....
 PISTON...*standard*.....
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE.....*1.10*...mm
 SHOCK LENGTH (X).....*10.6*...mm
 REBOUND *20%*.....

4° Yoke
 6° Yoke
 SERVO SAVER
 Yes No

Washers*0*...mm

Alloy Steel Double Joint