

DRIVER DETAILS

NAME Martin Hofer
 DATE 19.-21.7.13
 EVENT ETS #6 Trenchin SK
 WEATHER Hot!
 RESULT 3rd

NOTES

"hoff" steering plates, cut front wishbone



CHASSIS AND ELECTRICS

CHASSIS 2.5 Rear Motor Mid Motor
 TOP DECK 2.0, no front post
 BODYSHELL Speed 6 LW, 5mm forward
 WING MR33, 17 high, 10 over
 E.S.C handout
 SERVO GM HGM SLP (SHR mode)
 RECIEVER Sanwa 451R
 CELLS GM V-Maxx
 CELL POSITION Forward Middle Rearward

MOTOR AND GEARING

MOTOR handout
 ROTOR DIAMETER
 TIMING
 GEAR PITCH 48DP 64DP
 SPUR SIZE 96
 PINION SIZE 43

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C 35 °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS Ride
 TYRES REX34 handout
 INSERTS
 TYRE ADDITIVE Mighty
 ADDITIVE TIME Front 20 Minutes Rear 20 Minutes
 TYRE WARMERS Yes No Temp 65 °C Time 10 Minutes

REAR

Ball Diff
 Gear Diff
 Diff Oil 2000 cTs

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Droop..... 4.0 mm
 On 10mm Block
 Ride Height 5.0 mm
 Camber..... 2.0 Degree's
 Washers Under Ball
 Washers Under Bracket 2.0 mm
 Washers 0.5 mm

3 Groove 39mm
 4 Groove 37mm
 (4 Groove shown)

Washers 1.0 mm

0 Groove
 1 Groove
 2 Groove
 (2 Pip shown)

Washers 1.0 mm
 WheelBase
 Short
 Middle
 Long

CAP TYPE Vented Sealed Emulsion
 OIL..... 675 cTs
 SPRING..... Schumacher Green
 PISTON..... Standard
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1 mm
 SHOCK LENGTH (X)..... 10.5 mm
 REBOUND 20%

0 Pip 3.0°
 1 Pip 2.5°
 2 Pip 2.0°
 (2 Pip shown)

Alloy Steel

FRONT

Spool
 Gear Diff
 Diff Oil cTs

1.1mm - Yellow
 1.2mm - Red
 1.3mm - Green
 1.4mm - Blue
 1.5mm - Grey
 1.6mm - Orange

Washers Under Ball
 Washers Under Bracket 1.5 mm
 Droop..... 5.0 mm
 On 10mm Block
 Ride Height 4.8 mm
 Camber..... 1.5 Degree's
 Toe-in..... Degree's
 Toe-out..... 0.5 Degree's
 Washers 0.5 mm

3 Groove 39mm
 4 Groove 37mm
 (4 Groove shown)

Washers 0 mm

Washers 1.0 mm

Washers 1.0 mm
 WheelBase

CAP TYPE Vented Sealed Emulsion
 OIL..... 600 cTs
 SPRING..... Schumacher Green
 PISTON..... Standard
 DRILLED Yes No
 DRILLED PISTON HOLE SIZE..... 1.1 mm
 SHOCK LENGTH (X)..... 10.5 mm
 REBOUND 20%

4° Yoke
 6° Yoke
 SERVO SAVER
 Yes No

Washers 0 mm

Alloy Steel Double Joint