

### DRIVER DETAILS

NAME *Martin Hofer*  
 DATE -  
 EVENT *standard carpet setup*  
 WEATHER -  
 RESULT -

### NOTES

*cut front wishbones,  
 rear braces,  
 WildThing bits,*



### CHASSIS AND ELECTRICS

CHASSIS *2.0mm* Rear Motor  Mid Motor   
 TOP DECK *standard, no front post*  
 BODYSHELL *Pf speed 6 lw, 5mm forward*  
 WING *Schumacher, 17mm high, 10mm overhang*  
 E.S.C *GM*  
 SERVO *GM*  
 RECIEVER *Sanwa*  
 CELLS *GM*  
 CELL POSITION Forward  Middle  Rearward

### MOTOR AND GEARING

MOTOR *GM race 4.5*  
 ROTOR DIAMETER *std*  
 TIMING *std*  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE *114*  
 PINION SIZE *23*

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE °C  °F   
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS *CPX (0 notch rear hub plates with ride tires)*  
 TYRES -  
 INSERTS -  
 TYRE ADDITIVE *CS High Grip*  
 ADDITIVE TIME Front *15* Minutes Rear *15* Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### REAR

Ball Diff  
 Gear Diff  
 Diff Oil *3000* cTs

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

0 Pip 3.0°  
 1 Pip 2.5°  
 2 Pip 2.0°  
 (2 Pip shown)

Alloy  Steel

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Droop.....*4.0*...mm  
 On 10mm Block

Ride Height.....*5.2*...mm  
 Camber.....*2.0*...Degree's

Washers Under Ball  
 Washers Under Bracket  
 .....*1.5*...mm

Washers .....*0.5*...mm

Washers .....*0.5*...mm

0 Groove  
 1 Groove  
 2 Groove  
 (2 Pip shown)

Washers .....*1.0*...mm

WheelBase  
 Short  
 Middle  
 Long

0 Groove  
 1 Groove  
 2 Groove  
 (2 Pip shown)

Washers .....*1.0*...mm

WheelBase  
 Short  
 Middle  
 Long

CAP TYPE Vented  Sealed  Emulsion   
 OIL.....*450*...cTs  
 SPRING...*Yokomo blue*.....  
 PISTON...*standard*.....  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE.....*1.10*...mm  
 SHOCK LENGTH (X).....*10.5*...mm  
 REBOUND *20%*.....

### FRONT

Spool  
 Gear Diff  
 Diff Oil ..... cTs

3 Groove 39mm  
 4 Groove 37mm  
 (4 Groove shown)

4° Yoke  
 6° Yoke

Yes   
 No   
 SERVO SAVER

Alloy  Steel  Double Joint

1.1mm - Yellow  
 1.2mm - Red  
 1.3mm - Green  
 1.4mm - Blue  
 1.5mm - Grey  
 1.6mm - Orange

Washers Under Ball  
 Washers Under Bracket  
 .....*0.5*...mm

Droop.....*5.0*...mm  
 On 10mm Block

Ride Height.....*5.0*...mm  
 Camber.....*1.5*...Degree's  
 Toe-in..........Degree's  
 Toe-out.....*1.0*...Degree's

Washers .....*0.5*...mm

Washers .....*0*...mm

Washers .....*1.0*...mm

Washers .....*1.0*...mm

Washers .....*1.0*...mm

Washers .....*1.0*...mm

CAP TYPE Vented  Sealed  Emulsion   
 OIL.....*500*...cTs  
 SPRING...*Yokomo pink*.....  
 PISTON...*standard*.....  
 DRILLED Yes  No   
 DRILLED PISTON HOLE SIZE.....*1.10*...mm  
 SHOCK LENGTH (X).....*10.5*...mm  
 REBOUND *20%*.....