

### DRIVER DETAILS

NAME \_\_\_\_\_  
 DATE \_\_\_\_\_  
 EVENT \_\_\_\_\_  
 WEATHER \_\_\_\_\_  
 RESULT \_\_\_\_\_  
 FASTEST LAP TIME \_\_\_\_\_

### NOTES

TOP DECK CONNECTOR YES  NO



### CHASSIS AND ELECTRICS

CHASSIS Alloy  Carbon   
 TOP DECK 2.0mm  2.5mm  3.0mm  4.0mm   
 BODYSHELL \_\_\_\_\_  
 WING \_\_\_\_\_  
 E.S.C \_\_\_\_\_  
 SERVO \_\_\_\_\_  
 RECEIVER \_\_\_\_\_  
 CELLS \_\_\_\_\_

### MOTOR AND GEARING

MOTOR \_\_\_\_\_  
 ROTOR DIAMETER \_\_\_\_\_  
 TIMING \_\_\_\_\_  
 GEAR PITCH 48DP  64DP   
 SPUR SIZE \_\_\_\_\_  
 PINION SIZE \_\_\_\_\_

### TRACK CONDITIONS

GRIP LEVEL High  Medium  Low   
 TYPE Tight  Open  Mixed   
 SURFACE Carpet  Tarmac   
 CONDITION Smooth  Bumpy   
 TEMPERATURE \_\_\_\_\_ °C \_\_\_\_\_ °F  
 VENUE Indoor  Outdoor

### WHEELS, TYRES AND INSERTS

WHEELS \_\_\_\_\_  
 TYRES \_\_\_\_\_  
 INSERTS \_\_\_\_\_  
 TYRE ADDITIVE \_\_\_\_\_  
 ADDITIVE TIME Front Minutes Rear Minutes  
 TYRE WARMERS Yes  No  Temp °C Time Minutes

### FRONT

Spool  
 Gear Diff

Diff Oil ..... cTs

1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm  
 5 Dot - 1.5mm

Washers .....mm

Line In  Shims .....mm  
 Line Out  Shims .....mm

Droop.....mm  
 On 10mm Block   
 Ride Height .....mm  
 Camber.....°  
 Toe.....°  
 Pivot Block Strap

44.2  
 43.5  44.2  46.0

Washers .....mm  
 Washers.....mm

Washers .....mm

4° R  
 4° Yoke  
 6° Yoke

SERVO SAVER  
 Yes   
 No

Washers .....mm

12mm   
 13mm   
 14mm

Cap Type Vented  Sealed  Emulsion   
 Oil.....cTs  
 Spring.....  
 Piston.....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X).....mm  
 Rebound .....%

Peripheral Damping  
 Yes   
 No

Alloy  Steel  Double Joint

Narrow  
 Medium (kit)

Washers .....mm

### REAR

Diff Oil ..... cTs

48.1 .....mm  
 .....mm

0 Dot - 1.0mm  
 1 Dot - 1.1mm  
 2 Dot - 1.2mm  
 3 Dot - 1.3mm  
 4 Dot - 1.4mm

Medium  
 Wide (kit)

(2 Pip shown)  
 0 Groove  
 1 Groove  
 2 Groove

Droop.....mm  
 On 10mm Block   
 Ride Height .....mm  
 Camber.....°  
 Pivot Block Strap

Washers .....mm

44.2  45.5  46.1

Shims.....mm Shims .....mm

Line In   
 Line Out

Washers .....mm

Washers .....mm

WheelBase  
 Short  
 Middle  
 Long

Alloy  Steel

Cap Type Vented  Sealed  Emulsion   
 Oil.....cTs  
 Spring.....  
 Piston.....  
 Drilled Yes  No   
 Drilled piston Hole Size.....mm  
 Shock Length (X).....mm  
 Rebound .....%

Peripheral Damping  
 Yes   
 No