

DRIVER DETAILS

NAME Elliott Harper
 DATE 01/07/2017
 EVENT EFRA Euros Almussafes Spain
 WEATHER
 RESULT Q7, F6
 FASTEST LAP TIME

NOTES

TOP DECK CONNECTOR YES NO
 - Front toe out measured under load
 - Red o-rings in diff
 - Battery 1.0mm forward of centre
 - Both top deck posts
 - 2.25mm chassis



CHASSIS AND ELECTRICS

CHASSIS Alloy Carbon
 TOP DECK 2.0mm 2.5mm 3.0mm 4.0mm
 BODYSHELL PF LTC-R Lightweight
 WING Scumacher
 E.S.C LRP Flow X
 SERVO Sanwa
 RECEIVER Sanwa
 CELLS LRP 6400 LCG

MOTOR AND GEARING

MOTOR LRP X22 4.5
 ROTOR DIAMETER 12.5mm standard
 TIMING Middle
 GEAR PITCH 48DP 64DP
 SPUR SIZE 122
 PINION SIZE 30

TRACK CONDITIONS

GRIP LEVEL High Medium Low
 TYPE Tight Open Mixed
 SURFACE Carpet Tarmac
 CONDITION Smooth Bumpy
 TEMPERATURE °C °F
 VENUE Indoor Outdoor

WHEELS, TYRES AND INSERTS

WHEELS LRP G36
 TYRES LRP G36
 INSERTS LRP G36
 TYRE ADDITIVE
 ADDITIVE TIME Front Minutes Rear Minutes
 TYRE WARMERS Yes No Temp °C Time Minutes

FRONT

Diff Oil cTs

Spool
 Gear Diff

1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm
 5 Dot - 1.5mm

Washers 1.0mm
 Washers1.0 mm

Washers 0.5mm

Line In
 Line Out

Shims 0.5mm

Droop... 5.4mm
 On 10mm Block
 Ride Height... 5.2mm
 Camber... -1.5 °
 Toe... 1.2 out °
 Pivot Block Strap

43.5 44.2 46.0

4° R 4° Yoke
 6° Yoke

SERVO SAVER Yes No

Washers 2mm

12mm
 13mm
 14mm

Alloy Steel Double Joint

Narrow
 Medium (kit)

Washers 1.25mm

Cap Type Vented Sealed Emulsion
 Oil... Core RC 550cTs
 Spring... XKRAY 2.8
 Piston... 3 x 1.1mm
 Drilled Yes No
 Drilled piston Hole Size... 1.1mm
 Shock Length (X)... 11.3mm
 Rebound 0%

REAR

Diff Oil 2000 cTs

0 Dot - 1.0mm
 1 Dot - 1.1mm
 2 Dot - 1.2mm
 3 Dot - 1.3mm
 4 Dot - 1.4mm

Washers 1.5mm

Washers 0mm

Washers 1.0mm

WheelBase Short
 Middle
 Long

Medium
 Wide (kit)

Alloy Steel

Washers 1.0mm

Droop... 5.0mm
 On 10mm Block
 Ride Height... 5.4mm
 Camber... -2.0 °
 Pivot Block Strap

44.2 45.5 46.1

Shims 0.5mm

Cap Type Vented Sealed Emulsion
 Oil... Core RC 550cTs
 Spring... XKRAY 2.8
 Piston... 3 x 1.1mm
 Drilled Yes No
 Drilled piston Hole Size... 1.1mm
 Shock Length (X)... 11.3mm
 Rebound 0%